

MISSOURI PUBLIC SERVICE COMMISSION

STAFF's GAS INCIDENT REPORT

Appendix D

Exhibits

Spire Missouri Inc. d/b/a Spire Missouri West


Case No. GS-2021-0019

*Commission Staff Division
Safety Engineering Department
June 30, 2021 - Jefferson City, Missouri*

Knowing what to do in an emergency

In the event a natural gas pipeline is damaged, severe injury or death could occur. If you are ever involved in an emergency situation, please follow these steps:

- **Remove all ignition sources.** Turn off equipment and leave it in place. Do not light a match, start an engine, use a cell phone (in the area) or do anything that may create a spark.
- **Immediately leave the area and go to a safe location.** Move upwind and warn others to stay away from the area.
- **Call for help.** Once you are safely away from the area, call 911 for emergency assistance. Then call Spire's emergency number at 800-887-4173 in eastern Missouri and 800-582-1234 in western Missouri.
- **Never attempt to stop a leak.** Do not touch, attempt to repair or conceal a damaged pipeline.



Spire service area



Learn more about digging safely

Spire
[SpireEnergy.com](https://spireenergy.com)

811
call811.com

Common Ground Alliance
commongroundalliance.com

Missouri Common Ground Alliance
mocommground.org

Missouri Public Service Commission
psc.mo.gov

Office of Pipeline Safety
phmsa.dot.gov

USIC
usicllc.com

Heath Consultants
heathus.com

For more information about digging safely, contact us at **314-706-2399**. You can also visit www.commongroundalliance.com to learn more on damage prevention.

In case of an emergency, call us at **800-887-4173** in eastern Missouri or **800-582-1234** in western Missouri.

00473-MO-0319



Working together
to keep our
communities safe
What to know before you dig











Protecting our pipelines

Pipelines are one of the safest, most reliable forms of transporting natural gas and other petroleum products. And like any source of energy, it's important to always use caution when working around underground pipelines. So before beginning any excavation project, be sure to call 811 to confirm the position of underground facilities free of charge.

If you're working around underground pipelines, we encourage the use of "hand-dig/soft-dig" techniques to verify the exact location of all pipes before using any electric-powered equipment. You must also closely monitor the boring equipment during any excavation project.

If a gas pipeline is scratched, bumped or disturbed during an excavation project, reach out to us immediately at 314-706-2399 so we can assess the situation and prevent future safety hazards. In most cases, we will not pursue inspection or repair costs on disturbances that don't result in a gas leak.

The American Public Works Association (APWA) uses above-ground markers to identify underground utilities and alert people about future excavation activities in the area. These markers help keep our communities safe.

| | |
|---|---|
|  | White: Proposed excavation |
|  | Fluorescent Pink: Temporary survey markings |
|  | Red: Electric power lines, cables, conduit and lighting cables |
|  | Yellow: Gas, oil, steam, petroleum or gaseous materials |
|  | Orange: Communication, alarm or signal lines, cables or conduit |
|  | Blue: Potable water |
|  | Purple: Reclaimed water, irrigation and slurry lines |
|  | Green: Sewers and drain lines |

Working together to protect what matters most

The "Underground Facility Safety and Damage Prevention Act" (RSMo319), commonly referred to as the one-call law, requires everyone to call for facility marking before they dig.

You can stay safe by following these simple steps:

- 1 Make the call.**
Call 811 (national one-call number) and request that your project area be marked. The call and locating services are free of charge.
- 2 Wait the required time.**
Give utilities at least three working days to mark underground facilities. By law, a call is required no less than three working days and not more than 10 working days before digging starts.
- 3 Respect the marks.**
Spire natural gas facilities are marked with yellow paint and, if possible, with flags. If marks aren't clearly visible when starting your project, call 811 to have them marked again.
- 4 Dig with care.**
Remember to always verify the exact location and depth of gas facilities prior to digging with boring equipment and closely monitor the equipment during operations.

Monitoring and maintaining our pipelines

There's nothing more important than the safety of our community, so we take steps to monitor and maintain our pipeline system via aircraft, vehicle and on foot.

For instance, we use markers to show the general location of our pipelines. Markers are placed in prominent areas and at points where the pipeline changes direction. Because safety is our number one priority, emergency contact information is listed on each pipeline marker.



Instructions (rev 10-11-2018) for completing Form PHMSA F 7100.1-1 (rev 10-11-2018)

ANNUAL REPORT FOR CALENDAR YEAR 20_____

GAS DISTRIBUTION SYSTEM

12-3-2018 minor correction in Part G pending OMB approval

All section references are to Title 49 of the Code of Federal Regulations. Reporting requirements are contained in Part 191, "Transportation of Natural and Other Gas by Pipeline; Annual Reports, Incident Reports and Safety Related Condition Reports." Except as provided in §191.11(b), each operator of a gas distribution pipeline (see definitions below) must submit an annual report Form PHMSA F 7100.1-1 for the preceding calendar year not later than **March 15th**. Be sure to report TOTAL miles of main pipeline and services in the system at the end of the reporting year, including additions to the system during the year. The annual reporting period is on a calendar year basis ending on December 31st of each year.

If you need copies of the Form PHMSA F 7100.1-1 and/or instructions, they can be found on <http://www.phmsa.dot.gov/pipeline/library/forms>. The documents are included in the section titled Accident/Incident/Annual Reporting Forms.

ONLINE SUBMISSION IS REQUIRED UNLESS AN ALTERNATIVE REPORTING METHOD IS GRANTED BY PHMSA

ALTERNATE REPORTING METHOD

If electronic reporting imposes an undue burden and hardship, an operator may submit a written request for an alternative reporting method to the Information Resources Manager, Office of Pipeline Safety, Pipeline and Hazardous Materials Safety Administration, PHP-20, 1200 New Jersey Avenue, SE Washington DC 20590. The request must describe the undue burden and hardship. PHMSA will review the request and may authorize, in writing, an alternative reporting method. An authorization will state the period for which it is valid, which may be indefinite. An operator must contact PHMSA at 202-366-8075, or electronically to informationresourcesmanager@dot.gov or make arrangements for submitting a report that is due after a request for alternative reporting is submitted but before an authorization or denial is received.

ONLINE REPORTING METHOD

Annual Reports must be submitted online through the PHMSA Portal at <https://portal.phmsa.dot.gov/portal>, unless an alternate method is approved (see Alternate Reporting Methods below).

You will not be able to submit reports until you have met all of the Portal registration requirements – see http://opsweb.phmsa.dot.gov/portal_message/PHMSA_Portal_Registration.pdf. Completing these registration requirements could take several weeks. Plan ahead and register well in advance of the report due date.

Use the following procedure for online reporting:

1. Go to the PHMSA Portal at <https://portal.phmsa.dot.gov/portal>

Instructions (rev 10-11-2018) for completing Form PHMSA F 7100.1-1 (rev 10-11-2018)

ANNUAL REPORT FOR CALENDAR YEAR 20_____

GAS DISTRIBUTION SYSTEM

2. Enter PHMSA Portal Username and Password ; press *enter*
3. Select OPID; press “*continue*” button.
4. Under “**Create Reports**” on the left side of the screen, under *Annual* select “Gas Distribution” and proceed with entering your data. *Note: Data fields marked with a single asterisk are considered required fields that must be completed before the system will accept your initial submission.* Also, only one annual report by commodity for an OPID may be submitted per year.
5. To save intermediate work without formally submitting it to PHMSA, click **Save**. To modify a draft of an annual report that you saved, go to **Saved Reports** and click on *Gas Distribution*. Locate your saved report by the date, report year, or commodity. Select the record by clicking on it once, and then click **Modify** above the record.
6. Once all sections of the form have been completed, click on **Validate** to ensure all required fields have been completed and data meets all other requirements. A list of errors will be generated that must be fixed prior to submitting an Annual Report.
7. Click **Submit** when you have completed the Report (for either an Initial Report or a Supplemental Report), and are ready to initiate formal submission of your Report to PHMSA.
8. A confirmation message will appear that confirms a record has been successfully submitted. To save or print a copy of your submission, go to **Submitted Reports** on the left hand side, and click on *Gas Distribution*. Locate your submitted report by the date, report year, or Commodity Group, and then click on the PDF icon to either open the file and print it, or save an electronic copy.
9. To submit a *Supplemental Report*, go to **Submitted Reports** on the left hand side, and click on *Gas Distribution*. Locate your submitted report by the date, report year, or Commodity Group. Select the record by clicking on it once, and then click “Create Supplemental”.

GENERAL INSTRUCTIONS

The following definitions are from § 192.3:

1. “Distribution line” means a pipeline other than a gathering or transmission line.
2. “Gathering line” means a pipeline that transports gas from a current production facility to a transmission line or main.
3. “Transmission line” means a pipeline, other than a gathering line, that:
 - a. Transports gas from a gathering line or storage facility to a distribution center, storage facility, or large volume customer that is not downstream from a distribution center;
 - b. Operates at a hoop stress of 20 percent or more of SMYS; or

Case No. GS-2021-0019, APPENDIX D

Exhibit 2, Page 2 of 10

Instructions (rev 10-11-2018) for completing Form PHMSA F 7100.1-1 (rev 10-11-2018)

ANNUAL REPORT FOR CALENDAR YEAR 20_____

GAS DISTRIBUTION SYSTEM

- c. Transports gas within a storage field. A large volume customer may receive similar volumes of gas as a distribution center, and includes factories, power plants, and institutional users of gas.

4. “Operator” means a person who engages in the transportation of gas.

Make an entry in each block for which data are available. Estimate data if necessary. Avoid entering any data in the **UNKNOWN** columns, if possible. Some companies may have very old pipe for which installation records do not exist. Estimate the total of such mileage in the **UNKNOWN** column of Part B, item 2 “Miles of Main in System at End of Year” and item 3 “Number of Services in System at End of Year”, and item 4 “Miles of Main and Number of Services by Decade of Installation.”

Do not report miles of pipe, pipe segments, or pipeline in feet. When main miles and service counts for the same set of pipelines is reported in different parts of the form, the online system will require the different parts to be consistent. Main miles and service counts over 60 must be within 0.5% of the baseline and values under 60 must be within 0.3 miles for main and service counts must match exactly. Part B4, decade of installation, will serve as the baseline for main miles and service counts. For example, if you report 60 miles of main in Part B4, the miles of main in Parts B1 and B2 must be within 0.3 miles of 60. For main miles, use the number of decimal places needed to satisfy these consistency checks. Service counts may only be entered as positive integers.

For a given OPID, a separate Annual Report is required for each Commodity Group within that OPID. As an example, if an operator uses a single OPID and has one set of pipeline facilities transporting natural gas and another transporting landfill gas, this operator must file two Annual Reports – one Annual Report covering natural gas facilities and a second for the landfill gas facilities. When a pipeline facility transports two or more Commodity Groups, the pipeline facility should be reported only once under the predominantly transported Commodity Group.

PART A – OPERATOR INFORMATION

1. Name of Operator

This is the company name associated with the OPID. For online entries, the name will be automatically populated based on the OPID entered in A3. If the name that appears is not correct, you need to submit an Operator Name Change (Type A) Notification.

2. Location of Office Where Additional Information May Be Obtained

Enter the appropriate address.

3. Operator’s 5-digit Identification Number (OPID)

For online entries, the OPID will automatically populate based on the selection you made when entering the Portal. If you have log-in credentials for multiple OPID, be sure the report is being created for the appropriate OPID. Contact PHMSA’s Operator Hotline at 202-366-8075 if you need assistance with an OPID.

Instructions (rev 10-11-2018) for completing Form PHMSA F 7100.1-1 (rev 10-11-2018)

ANNUAL REPORT FOR CALENDAR YEAR 20_____

GAS DISTRIBUTION SYSTEM

4. Headquarters Name and Address

This is the headquarters address associated with the OPID. For online entries, the address will automatically populate based on the OPID entered in A3. If the address that appears is not correct, you need to change it in the online Contacts module.

5. State of Operation

Enter the **State for which information is being reported. Submit a separate report for each State** in which the company operates a gas distribution pipeline system.

6. Commodity Group

It is a PHMSA requirement that operators submit separate Reports for each Commodity Group within a particular OPID.

File a separate Annual Report for each of the following Commodity Groups:

Natural Gas

Synthetic Gas (such as manufactured gas based on naphtha)

Hydrogen Gas

Propane Gas

Landfill Gas (includes biogas)

Other Gas – If this Commodity Group is selected, report the name of the other gas in the space provided.

Note: When a pipeline facility transports two or more of the above Commodity Groups, the pipeline facility should be reported only once under the predominantly transported Commodity Group. For example, if an operator has a pipeline segment that is used to transport natural gas during the majority of the year and propane for a couple of weeks, that operator should only file an annual report for the natural gas. If an operator has two pipeline segments with one pipeline segment used to transport natural gas and the other pipeline segment transporting hydrogen gas, that operator should file two annual reports - 1 report for natural gas and 1 report for hydrogen gas.

7. Operator Type

Enter the Type of Operator based on the structure of the company included in this OPID for which this report is being submitted. “Investor Owned” means the operator is controlled by a corporation with publicly traded stock. “Municipally Owned” means the operator is controlled by any type of State or local government entity including, county, parish, utility district, or municipality. “Privately Owned”

Instructions (rev 10-11-2018) for completing Form PHMSA F 7100.1-1 (rev 10-11-2018)

ANNUAL REPORT FOR CALENDAR YEAR 20_____

GAS DISTRIBUTION SYSTEM

means the operator is controlled by a corporation without publicly traded stock. All other operators should report “Cooperative.”

PART B – SYSTEM DESCRIPTION

“Coated” means pipe coated with any effective hot or cold applied dielectric coating or wrapper.

“Reconditioned Cast Iron” means cast iron gas distribution pipe that has been lined internally by use of suitable materials that ensure safe operation at an MAOP not to exceed the previously established MAOP. “Reconditioned Cast Iron” does not include cast iron pipe inserted with a gas pipe that is, by itself, suitable for gas service under Part 192, e.g., an ASTM D2513 pipe meeting code requirements for the intended gas service. Such insertions shall be reported as the material used in the insertion. The intent of the definition is to make a clear distinction between a liner and inserted pipe. An example of “Reconditioned Cast Iron” would be the insertion of a liner inside cast iron pipe where the liner relies on the structural integrity of the cast iron pipe. For details on liner insertion, see ASTM F2207, Standard Specification for Cured-in-Place Pipe Lining System for Rehabilitation of Metallic Gas Pipe. Methods of installation like pipe-splitting or bursting that involve the installation of a new stand-alone pipe while the host pipe is destroyed does not result in “Reconditioned Cast Iron”.

“PVC” means polyvinyl chloride plastic.

“PE” means polyethylene plastic.

“ABS” means acrylonitrile-butadiene-styrene plastic.

“Cathodically protected” applies to both “bare” and “coated.”

“Other” means a pipe of any material not specifically designated on the form. If you enter miles of main or services in the “other” category, describe these materials in the appropriate text box.

“Number of service” is the number of service lines, not the number of customers served.

Provide miles of main and numbers of services by decade installed in Part B, section 4.

If you do not know the decade of installation of the pipe because there are no records containing such information, enter an estimate in the UNKNOWN column. The sum total of mileage and number of services reported for Part B, section 4 must be consistent with total mileage and number of services reported in sections 1, 2, and 3 in Part B.

PART C – TOTAL LEAKS AND HAZARDOUS LEAKS ELIMINATED/REPAIRED DURING YEAR

In the appropriate column, include the total number of leaks and the number of hazardous leaks eliminated by repair, replacement or other action during the reporting year. The number of “hazardous leaks” eliminated or repaired during the year is reported as a performance measure for integrity management per § 192.1007(g). When reporting leaks or hazardous leaks eliminated by replacing or

Case No. GS-2021-0019, APPENDIX D

Exhibit 2, Page 5 of 10

Instructions (rev 10-11-2018) for completing Form PHMSA F 7100.1-1 (rev 10-11-2018)

ANNUAL REPORT FOR CALENDAR YEAR 20_____

GAS DISTRIBUTION SYSTEM

abandoning a segment of pipe, count the leaks that existed in the pipe segment before it was replaced or abandoned. Also include leaks and hazardous leaks reported on form PHMSA 7100.1, "Incident Report Gas Distribution Systems." A reportable incident is one described in § 191.3. Do not include leaks that occurred during testing.

A "leak" is defined as an unintentional escape of gas from the pipeline. Do NOT report a leak determined to be non-hazardous and eliminated by lubrication, adjustment, or tightening.

A "hazardous leak" means a leak that represents an existing or probable hazard to persons or property and requires immediate repair or continuous action until the conditions are no longer hazardous. A "hazardous leak" which occurs aboveground or belowground is a leak and must be reported.

Operators who do not grade leaks for hazard, but rather repair all leaks when found, need not grade repaired leaks solely for the purpose of this report. Such operators treat all leaks as if hazardous. Operators who do not grade leaks must report the same values for both total and hazardous leaks for each cause.

The "number of known system leaks at the end of the year scheduled for repair" is the total number pipeline system leaks being monitored and scheduled for repair at the end of the calendar year. Monitored leaks also include those leaks which have been temporarily repaired until a permanent repair can be performed. These leaks are non-hazardous unless reclassified following the operator's operation and maintenance procedures.

Leak causes are classified as:

CORROSION FAILURE: leak caused by galvanic, atmospheric, stray current, microbiological, or other corrosive action. A corrosion release or failure is not limited to a hole in the pipe or other piece of equipment. If the bonnet or packing gland on a valve or flange on piping deteriorates or becomes loose and leaks due to corrosion and failure of bolts, it is classified as Corrosion. (Note: If the bonnet, packing, or other gasket has deteriorated to failure, whether before or after the end of its expected life, but not due to corrosive action, report it under a different cause category, such as G4 Incorrect Operation for improper installation or G6 Equipment Failure if the gasket failed)

NATURAL FORCE DAMAGE: leak caused by outside forces attributable to causes NOT involving humans, such as earth movement, earthquakes, landslides, subsidence, heavy rains/floods, lightning, temperature, thermal stress, frozen components, high winds (Including damage caused by impact from objects blown by wind), or other similar natural causes. Lightning includes both damage and/or fire caused by a direct lightning strike and damage and/or fire as a secondary effect from a lightning strike in the area. An example of such a secondary effect would be a forest fire started by lightning that results in damage to a gas distribution system asset which results in an incident.

EXCAVATION DAMAGE: leak resulting directly from excavation damage by operator's personnel (oftentimes referred to as "first party" excavation damage) or by the operator's contractor (oftentimes referred to as "second party" excavation damage) or by people or contractors not associated with the operator (oftentimes referred to as "third party" excavation damage). Also, this section includes a release or failure determined to have resulted from previous damage due to excavation activity. For damage

Case No. GS-2021-0019, APPENDIX D

Exhibit 2, Page 6 of 10

Instructions (rev 10-11-2018) for completing Form PHMSA F 7100.1-1 (rev 10-11-2018)

ANNUAL REPORT FOR CALENDAR YEAR 20_____

GAS DISTRIBUTION SYSTEM

from outside forces OTHER than excavation which results in a release, use Natural Force Damage or Other Outside Force, as appropriate.

OTHER OUTSIDE FORCE DAMAGE: leak resulting from outside force damage, other than excavation damage or natural forces such as:

- Nearby Industrial, Man-made or Other Fire/Explosion as Primary Cause of Incident (unless the fire was caused by natural forces, in which case the leak should be classified Natural Forces. Forest fires that are caused by human activity and result in a release should be reported as Other Outside Force),
- Damage by Car, Truck, or Other Motorized Vehicle/Equipment NOT Engaged in Excavation. Other motorized vehicles/equipment includes tractors, mowers, backhoes, bulldozers and other tracked vehicles, and heavy equipment that can move. Leaks resulting from vehicular traffic loading or other contact (except report as “Excavation Damage” if the activity involved digging, drilling, boring, grading, cultivation or similar activities.
- Damage by Boats, Barges, Drilling Rigs, or Other Maritime Equipment or Vessels so long as those activities are not excavation activities. If those activities are excavation activities such as dredging or bank stabilization or renewal, the leak repair should be reported as “Excavation Damage”.
- Previous Mechanical Damage NOT Related to Excavation. A leak caused by damage that occurred at some time prior to the release that was apparently NOT related to excavation activities, and would include prior outside force damage of an unknown nature, prior natural force damage, prior damage from other outside forces, and any other previous mechanical damage other than that which was apparently related to prior excavation. Leaks resulting from previous damage sustained during construction, installation, or fabrication of the pipe, weld, or joint from which the release eventually occurred are to be reported under “Pipe, Weld, or Joint Failure”. Leaks resulting from previous damage sustained as a result of excavation activities should be reported under “Excavation Damage” unless due to corrosion in which case it should be reported as a corrosion leak.
- Intentional Damage/. Vandalism means willful or malicious destruction of the operator’s pipeline facility or equipment. This category would include pranks, systematic damage inflicted to harass the operator, motor vehicle damage that was inflicted intentionally, and a variety of other intentional acts.
- Terrorism, per 28 C.F.R. § 0.85 General functions, includes the unlawful use of force and violence against persons or property to intimidate or coerce a government, the civilian population, or any segment thereof, in furtherance of political or social objectives.
- Theft. Theft means damage by any individual or entity, by any mechanism, specifically to steal, or attempt to steal, the transported gas or pipeline equipment.

PIPE, WELD, OR JOINT FAILURE : Leak resulting from a material defect within the pipe, component or joint due to faulty manufacturing procedures, design defects, or in-service stresses such as vibration, fatigue and environmental cracking. Material defect means an inherent flaw in the material or weld that occurred in the manufacture or at a point prior to construction, fabrication or installation. Design defect means an aspect inherent in a component to which a subsequent failure has been attributed that is not associated with errors in installation, i.e., is not a construction defect. This could include, for example, errors in engineering design. Fitting means a device, usually metal, for joining lengths of pipe into various piping systems. It includes couplings, ells, tees, crosses, reducers, unions, caps and plugs. Any leak that is associated with a component or process that joins pipe such as threaded connections, flanges, mechanical couplings, welds, and pipe fusions that leak as a result from poor construction should be classified as “Incorrect Operation”. Leaks resulting from failure of original sound material from force

Case No. GS-2021-0019, APPENDIX D

Exhibit 2, Page 7 of 10

Instructions (rev 10-11-2018) for completing Form PHMSA F 7100.1-1 (rev 10-11-2018)

ANNUAL REPORT FOR CALENDAR YEAR 20_____

GAS DISTRIBUTION SYSTEM

applied during construction that caused a dent, gouge, excessive stress, or other defect, including leaks due to faulty wrinkle bends, faulty field welds, and damage sustained in transportation to the construction or fabrication site that eventually resulted in a leak, should be reported as “Pipe, Weld or Joint Failure”.

EQUIPMENT FAILURE: leak caused by malfunctions of control and relief equipment including regulators, valves, meters, compressors, or other instrumentation or functional equipment. Failures may be from threaded components, Flanges, collars, couplings and broken or cracked components, or from O- Ring failures, Gasket failures, seal failures, and failures in packing or similar leaks. Leaks caused by overpressurization resulting from malfunction of control or alarm device; relief valve malfunction: and valves failing to open or close on command; or valves which opened or closed when not commanded to do so. If overpressurization or some other aspect of this incident was caused by incorrect operation, the incident should be reported under “Incorrect Operation.”

INCORRECT OPERATION: leak resulting from inadequate procedures or safety practices, or failure to follow correct procedures, or other operator error. It includes leaks due to improper valve selection or operation, inadvertent overpressurization, or improper selection or installation of equipment. It includes a leak resulting from the unintentional ignition of the transported gas during a welding or maintenance activity.

OTHER CAUSE: leak resulting from any other cause not attributable to the above causes. A best effort should be made to assign a specific leak cause before choosing the Other cause category. An operator replacing a bare steel pipeline with a history of external corrosion leaks without visual observation of the actual leak, may form a hypothesis based on available information that the leak was caused by external corrosion and assign the Corrosion cause category to the leak.

PART D – EXCAVATION DAMAGE

Excavation damages are reported as a measure of the effectiveness of integrity management programs (§ 192.1007(g)).

Report the “Number of Excavation Damages” experienced during the calendar year by the following apparent root cause which are classified as:

One-Call Notification Practices Not Sufficient: Damages resulting from no notification made to the One-Call Center; or notification to one-call center made, but not sufficient; or wrong information provided to One Call Center.

Locating Practices Not Sufficient: Damages resulting from facility could not be found or located; or facility marking or location not sufficient; or facility was not located or marked; or incorrect facility records/maps.

Excavation Practices Not Sufficient: Damages resulting from failure to maintain marks; or failure to support exposed facilities; or failure to use hand tools where required; or failure to test-hole (pot-hole); or improper backfilling practices; or failure to maintain clearance; or other insufficient excavation practices.

Instructions (rev 10-11-2018) for completing Form PHMSA F 7100.1-1 (rev 10-11-2018)

ANNUAL REPORT FOR CALENDAR YEAR 20_____

GAS DISTRIBUTION SYSTEM

Other: Damages resulting from One-Call Center error; or abandoned facility; or deteriorated facility; or previous damage or data not collected; or other.

The Total Number of Excavation Damages will be calculated automatically based on the data entered. For this purpose, "Excavation Damage" means any impact that results in the need to repair or replace an underground facility due to a weakening, or the partial or complete destruction, of the facility, including, but not limited to, the protective coating, plastic pipe tracer wire, lateral support, cathodic protection or the housing for the line device or facility.

Report also the "Number of Excavation Tickets" received during the year, (i.e., receipt of information by the operator from the notification center).

PART E – EXCESS FLOW VALVE (EFV) AND SERVICE VALVE DATA

Report the number of EFV and manual service line shut-off valves installed during the calendar year. Report the estimated total number of EFV and manual service line shut-off valves in the system at the end of the calendar reporting year. Be sure to include the number installed during the calendar year when reporting the estimated number in the system at the end of the calendar year.

PART F – TOTAL NUMBER OF LEAKS ON FEDERAL LAND REPAIRED/ELIMINATED OR SCHEDULED FOR REPAIR

Federal Lands: As defined in 30 U.S.C. §185, federal lands means "all lands owned by the United States except lands in the National Park System, lands held in trust for an Indian or Indian tribe, and lands on the Outer Continental Shelf." Indicate only those leaks repaired, eliminated, or scheduled for repair during the reporting year, including those incidents reported on Form PHMSA F 7100.1.

PART G – PERCENT OF UNACCOUNTED FOR GAS

"Unaccounted for gas" is gas lost; that is, gas that the operator cannot account for as usage or through appropriate adjustment. Adjustments are appropriately made for such factors as variations in temperature, pressure, meter-reading cycles, or heat content; calculable losses from construction, purging, line breaks, etc., where specific data are available to allow reasonable calculation or estimate; or other similar factors.

State the amount of unaccounted for gas as a percent of total consumption for the 12 months ending June 30 of the reporting year.

[(Purchased gas + produced gas) minus (customer use + company use + appropriate adjustments)] divided by (customer use + company use + appropriate adjustments) times 100 equals percent unaccounted for.

Instructions (rev 10-11-2018) for completing Form PHMSA F 7100.1-1 (rev 10-11-2018)
ANNUAL REPORT FOR CALENDAR YEAR 20_____
GAS DISTRIBUTION SYSTEM

PART H – ADDITIONAL INFORMATION

Include any additional information which will assist in clarifying or classifying the reported data.

PART I - PREPARER

PREPARER is the name of the person most knowledgeable about the report or the person to be contacted for more information. Please include the direct phone number and email address as applicable (e-mail address is desired but not required). It should be noted that PHMSA will use your e-mail address to issue correspondence that is normally sent via mass mailings. "Correspondence" includes notifications such as the annual reminder letter for Annual Report filings.