

Settle3D Analysis Information

Labadie UWL

Project Settings

Document Name: circle 47.s3z
 Project Title: Labadie UWL
 Analysis: Settlement
 Author: Christopher Cook
 Company: Reitz & Jens, Inc
 Date Created: 10/17/2012, 11:48:36 AM
 Stress Computation Method: Boussinesq
 Use average properties to calculate layered stresses
 Groundwater method: Water Table
 Water Unit Weight: 0.0624 kips/ft³
 Depth to water table: 1 [ft]

Stage Settings

| Stage # | Name |
|---------|---------|
| 1 | Stage 1 |

Results

Time taken to compute: 0 seconds

Stage: Stage 1

| Data Type | Minimum | Maximum |
|------------------------------------|-----------|----------|
| Total Settlement [in] | 0 | 20.9532 |
| Consolidation Settlement [in] | 0 | 7.85148 |
| Immediate Settlement [in] | 0 | 13.1102 |
| Loading Stress [ksf] | 0 | 10.3292 |
| Effective Stress [ksf] | 0 | 16.4014 |
| Total Stress [ksf] | 0 | 22.7662 |
| Total Strain | 0 | 0.083698 |
| Pore Water Pressure [ksf] | 0 | 6.3648 |
| Degree of Consolidation [%] | 0 | 100 |
| Pre-consolidation Stress [ksf] | 0.0585001 | 16.3699 |
| Over-consolidation Ratio | 1 | 9.15019 |
| Void Ratio | 0 | 0.916997 |
| Hydroconsolidation Settlement [in] | 0 | 0 |

Loads

1. Polygonal Load

Load Type: Flexible
Area of Load: 183389 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1929.25 | 862.473 | 0 |
| -1332.07 | -407.189 | 0 |
| -210.328 | -424.303 | 0 |
| -270.312 | -363.597 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -1870.41 | 874.203 | 2.9 |
| -1852.31 | 1508.1 | 2.9 |
| -1908.21 | 1557.97 | 0 |

2. Polygonal Load

Load Type: Flexible
Area of Load: 234768 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -221.212 | 1808.9 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -210.328 | -424.303 | 0 |
| -162.623 | 1880.73 | 0 |
| -1908.21 | 1557.97 | 0 |

3. Polygonal Load

Load Type: Flexible
Area of Load: 156632 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1870.41 | 874.203 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -317.264 | -315.23 | 5 |
| -1259.26 | -297.655 | 5 |
| -1809.13 | 885.67 | 5 |
| -1806.79 | 1469.02 | 5 |
| -1852.31 | 1508.1 | 2.9 |

4. Polygonal Load

Load Type: Flexible
Area of Load: 171981 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -1806.79 | 1469.02 | 5 |
| -267.217 | 1755.15 | 5 |
| -317.264 | -315.23 | 5 |
| -270.312 | -363.597 | 2.9 |
| -221.212 | 1808.9 | 2.9 |

5. Polygonal Load

Load Type: Flexible
Area of Load: 244557 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -102.643 | -2757.4 | 0 |
| 1076.16 | -2794.88 | 0 |
| 1109.25 | -1637.87 | 0 |
| 3035.41 | -1668.34 | 0 |
| 2874.5 | -1608.34 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 1016.65 | -2734.4 | 2.9 |
| -39.0646 | -2705.7 | 2.9 |

6. Polygonal Load

Load Type: Flexible
Area of Load: 433982 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0604 | -2705.58 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 3035.41 | -1668.34 | 0 |
| 35.4746 | 897.295 | 0 |
| -102.643 | -2757.4 | 0 |

7. Polygonal Load

Load Type: Flexible
Area of Load: 451309 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| 27.8223 | -2642.81 | 5 |
| 153.042 | 647.667 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2874.5 | -1608.34 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| -39.0604 | -2705.58 | 2.9 |

8. Polygonal Load

Load Type: Flexible
Area of Load: 238713 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0644 | -2705.7 | 2.9 |
| 1018.23 | -2734.44 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 2690.18 | -1545.21 | 5 |
| 989.752 | -1516.32 | 5 |
| 956.638 | -2672.65 | 5 |
| 27.8223 | -2642.81 | 5 |

9. Polygonal Load

Load Type: Flexible
Area of Load: 567821 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1637.57 | 1323.75 | 10.2 |
| -447.535 | 1544.49 | 10.2 |
| -485.349 | -142.076 | 10.2 |
| -317.264 | -315.23 | 10.2 |
| -267.217 | 1755.15 | 5 |
| -1806.56 | 1468.98 | 5 |

10. Polygonal Load

Load Type: Flexible
Area of Load: 1.5903e+006 ft²

Load: 10.2 ksf
Depth: 0 ft
Installation Stage: Stage 1

Coordinates

| X [ft] | Y [ft] |
|----------|----------|
| -1649.21 | 915.592 |
| -1153.62 | -131.529 |
| -485.349 | -142.076 |
| -447.535 | 1544.49 |
| -1637.57 | 1323.75 |

11. Polygonal Load

Load Type: Flexible
Area of Load: 417396 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -485.349 | -142.076 | 10.2 |
| -1153.62 | -131.529 | 10.2 |
| -1649.21 | 915.592 | 10.2 |
| -1637.57 | 1323.75 | 10.2 |
| -1806.56 | 1468.98 | 5 |
| -1809.13 | 885.67 | 5 |
| -1259.26 | -297.655 | 5 |
| -317.264 | -315.23 | 5 |

12. Polygonal Load

Load Type: Flexible
Area of Load: 941302 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 188.83 | -2491.7 | 10.2 |
| 293.799 | 364.216 | 10.2 |
| 2201.69 | -1376.73 | 10.2 |
| 2690.18 | -1545.21 | 5 |
| 153.042 | 647.667 | 5 |
| 27.7015 | -2645.99 | 5 |

13. Polygonal Load

Load Type: Flexible
Area of Load: 551990 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 952.602 | -2672.52 | 5 |
| 989.748 | -1516.48 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2201.69 | -1376.73 | 10.2 |
| 832.524 | -1353.16 | 10.2 |
| 802.744 | -2507.54 | 10.2 |
| 188.83 | -2491.7 | 10.2 |
| 27.7015 | -2645.99 | 5 |

14. Polygonal Load

Load Type: Flexible

Area of Load: 2.38333e+006 ft²

Depth: 0 ft


Installation Stage: Stage 1

Coordinates and Load






| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 832.524 | -1353.16 | 10.2 |
| 2201.69 | -1376.73 | 10.2 |
| 293.799 | 364.216 | 10.2 |
| 188.83 | -2491.7 | 10.2 |
| 802.744 | -2507.54 | 10.2 |

Soil Layers

| Layer # | Type | Thickness [ft] | Depth [ft] |
|---------|---------------|----------------|------------|
| 1 | SILT | 7 | 0 |
| 2 | CLAY | 8 | 7 |
| 3 | SAND & SILT | 8.5 | 15 |
| 4 | SAND | 16.5 | 23.5 |
| 5 | SAND & GRAVEL | 63 | 40 |



Soil Properties

| Property | CLAY | SILT | SAND & SILT | SAND | SAND & GRAVEL |
|---|---|---|---|--|---|
| Color |  |  |  |  |  |
| Unit Weight [kips/ft ³] | 0.113 | 0.117 | 0.122 | 0.122 | 0.124 |
| Saturated Unit Weight [kips/ft ³] | 0.113 | 0.117 | 0.122 | 0.122 | 0.124 |
| Immediate Settlement | Disabled | Enabled | Enabled | Enabled | Enabled |
| Es [ksf] | | 200 | 700 | 1100 | 1400 |
| E _{sur} [ksf] | | 200 | 700 | 1100 | 1400 |
| Primary Consolidation | Enabled | Disabled | Disabled | Disabled | Disabled |
| Material Type | Non-Linear | | | | |
| C _c | 0.3 | | | | |
| C _r | 0.05 | | | | |
| e ₀ | 0.917 | | | | |
| P _c [ksf] | 4.52 | | | | |
| OCR | | 1 | 1 | 1 | 1 |
| Secondary Consolidation | Standard | Disabled | Disabled | Disabled | Disabled |
| C _{ae} /C _a | 0.005 | | | | |
| C _{ar} /C _{are} | 0.005 | | | | |

Query Lines

| Line # | Start Location | End Location | Horizontal Divisions | Vertical Divisions |
|--------|-------------------|-------------------|----------------------|--------------------|
| 1 | -2058.82, 801.176 | -110.756, 801.176 | 100 | 101 |

Settle3D Analysis Information

Labadie UWL

Project Settings

Document Name: CIRCLE 48.s3z
 Project Title: Labadie UWL
 Analysis: Settlement
 Author: Christopher Cook
 Company: Reitz & Jens, Inc
 Date Created: 10/17/2012, 11:48:36 AM
 Stress Computation Method: Boussinesq
 Use average properties to calculate layered stresses
 Groundwater method: Water Table
 Water Unit Weight: 0.0624 kips/ft³
 Depth to water table: 1 [ft]

Stage Settings

| Stage # | Name |
|---------|---------|
| 1 | Stage 1 |

Results

Time taken to compute: 0 seconds

Stage: Stage 1

| Data Type | Minimum | Maximum |
|------------------------------------|-------------|-----------|
| Total Settlement [in] | 0 | 20.4739 |
| Consolidation Settlement [in] | 0 | 7.35604 |
| Immediate Settlement [in] | 0 | 13.1178 |
| Loading Stress [ksf] | 0 | 10.2043 |
| Effective Stress [ksf] | 0 | 16.5216 |
| Total Stress [ksf] | 0 | 23.0112 |
| Total Strain | 3.9992e-008 | 0.0983004 |
| Pore Water Pressure [ksf] | 0 | 6.4896 |
| Degree of Consolidation [%] | 0 | 100 |
| Pre-consolidation Stress [ksf] | 0.506464 | 16.4897 |
| Over-consolidation Ratio | 1 | 80.6776 |
| Void Ratio | 0 | 0.862 |
| Hydroconsolidation Settlement [in] | 0 | 0 |

Loads

1. Polygonal Load

Load Type: Flexible
Area of Load: 183389 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1929.25 | 862.473 | 0 |
| -1332.07 | -407.189 | 0 |
| -210.328 | -424.303 | 0 |
| -270.312 | -363.597 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -1870.41 | 874.203 | 2.9 |
| -1852.31 | 1508.1 | 2.9 |
| -1908.21 | 1557.97 | 0 |

2. Polygonal Load

Load Type: Flexible
Area of Load: 234768 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -221.212 | 1808.9 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -210.328 | -424.303 | 0 |
| -162.623 | 1880.73 | 0 |
| -1908.21 | 1557.97 | 0 |

3. Polygonal Load

Load Type: Flexible
Area of Load: 156632 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1870.41 | 874.203 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -317.264 | -315.23 | 5 |
| -1259.26 | -297.655 | 5 |
| -1809.13 | 885.67 | 5 |
| -1806.79 | 1469.02 | 5 |
| -1852.31 | 1508.1 | 2.9 |

4. Polygonal Load

Load Type: Flexible
Area of Load: 171981 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -1806.79 | 1469.02 | 5 |
| -267.217 | 1755.15 | 5 |
| -317.264 | -315.23 | 5 |
| -270.312 | -363.597 | 2.9 |
| -221.212 | 1808.9 | 2.9 |

5. Polygonal Load

Load Type: Flexible
Area of Load: 244557 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -102.643 | -2757.4 | 0 |
| 1076.16 | -2794.88 | 0 |
| 1109.25 | -1637.87 | 0 |
| 3035.41 | -1668.34 | 0 |
| 2874.5 | -1608.34 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 1016.65 | -2734.4 | 2.9 |
| -39.0646 | -2705.7 | 2.9 |

6. Polygonal Load

Load Type: Flexible
Area of Load: 433982 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0604 | -2705.58 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 3035.41 | -1668.34 | 0 |
| 35.4746 | 897.295 | 0 |
| -102.643 | -2757.4 | 0 |

7. Polygonal Load

Load Type: Flexible
Area of Load: 451309 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| 27.8223 | -2642.81 | 5 |
| 153.042 | 647.667 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2874.5 | -1608.34 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| -39.0604 | -2705.58 | 2.9 |

8. Polygonal Load

Load Type: Flexible
Area of Load: 238713 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0644 | -2705.7 | 2.9 |
| 1018.23 | -2734.44 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 2690.18 | -1545.21 | 5 |
| 989.752 | -1516.32 | 5 |
| 956.638 | -2672.65 | 5 |
| 27.8223 | -2642.81 | 5 |

9. Polygonal Load

Load Type: Flexible
Area of Load: 567821 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1637.57 | 1323.75 | 10.2 |
| -447.535 | 1544.49 | 10.2 |
| -485.349 | -142.076 | 10.2 |
| -317.264 | -315.23 | 10.2 |
| -267.217 | 1755.15 | 5 |
| -1806.56 | 1468.98 | 5 |

10. Polygonal Load

Load Type: Flexible
Area of Load: 1.5903e+006 ft²

Load: 10.2 ksf
Depth: 0 ft
Installation Stage: Stage 1

Coordinates

| X [ft] | Y [ft] |
|----------|----------|
| -1649.21 | 915.592 |
| -1153.62 | -131.529 |
| -485.349 | -142.076 |
| -447.535 | 1544.49 |
| -1637.57 | 1323.75 |

11. Polygonal Load

Load Type: Flexible
Area of Load: 417396 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -485.349 | -142.076 | 10.2 |
| -1153.62 | -131.529 | 10.2 |
| -1649.21 | 915.592 | 10.2 |
| -1637.57 | 1323.75 | 10.2 |
| -1806.56 | 1468.98 | 5 |
| -1809.13 | 885.67 | 5 |
| -1259.26 | -297.655 | 5 |
| -317.264 | -315.23 | 5 |

12. Polygonal Load

Load Type: Flexible
Area of Load: 941302 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 188.83 | -2491.7 | 10.2 |
| 293.799 | 364.216 | 10.2 |
| 2201.69 | -1376.73 | 10.2 |
| 2690.18 | -1545.21 | 5 |
| 153.042 | 647.667 | 5 |
| 27.7015 | -2645.99 | 5 |

13. Polygonal Load

Load Type: Flexible
Area of Load: 551990 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 952.602 | -2672.52 | 5 |
| 989.748 | -1516.48 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2201.69 | -1376.73 | 10.2 |
| 832.524 | -1353.16 | 10.2 |
| 802.744 | -2507.54 | 10.2 |
| 188.83 | -2491.7 | 10.2 |
| 27.7015 | -2645.99 | 5 |

14. Polygonal Load

Load Type: Flexible

Area of Load: 2.38333e+006 ft²

Depth: 0 ft


Installation Stage: Stage 1

Coordinates and Load






| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 832.524 | -1353.16 | 10.2 |
| 2201.69 | -1376.73 | 10.2 |
| 293.799 | 364.216 | 10.2 |
| 188.83 | -2491.7 | 10.2 |
| 802.744 | -2507.54 | 10.2 |

Soil Layers

| Layer # | Type | Thickness [ft] | Depth [ft] |
|---------|---------------|----------------|------------|
| 1 | CLAY | 7 | 0 |
| 2 | SILT | 7 | 7 |
| 3 | SILT & SAND | 8 | 14 |
| 4 | SAND | 23 | 22 |
| 5 | SAND & GRAVEL | 60 | 45 |



Soil Properties

| Property | CLAY | SILT | SILT & SAND | SAND | SAND & GRAVEL |
|---|---|---|---|--|---|
| Color |  |  |  |  |  |
| Unit Weight [kips/ft ³] | 0.118 | 0.117 | 0.12 | 0.122 | 0.124 |
| Saturated Unit Weight [kips/ft ³] | 0.118 | 0.117 | 0.12 | 0.122 | 0.124 |
| Immediate Settlement | Disabled | Enabled | Enabled | Enabled | Enabled |
| Es [ksf] | | 150 | 700 | 900 | 1400 |
| Es bottom [ksf] | | 400 | | | |
| Esur [ksf] | | 150 | 700 | 900 | 1400 |
| Esur bottom [ksf] | | 400 | | | |
| Primary Consolidation | Enabled | Disabled | Disabled | Disabled | Disabled |
| Material Type | Non-Linear | | | | |
| Cc | 0.32 | | | | |
| Cr | 0.04 | | | | |
| e0 | 0.862 | | | | |
| Pc [ksf] | 4.76 | | | | |
| OCR | | 1 | 1 | 1 | 1 |
| Secondary Consolidation | Standard | Disabled | Disabled | Disabled | Disabled |
| Cae/Ca | 0.004 | | | | |
| Car/Care | 0.004 | | | | |

Query Lines

| Line # | Start Location | End Location | Horizontal Divisions | Vertical Divisions |
|--------|-------------------|------------------|----------------------|--------------------|
| 1 | -119.939, -437.96 | 1670.82, -437.96 | 100 | 101 |

Settle3D Analysis Information

Labadie UWL

Project Settings

Document Name: CIRCLE 49.s3z
 Project Title: Labadie UWL
 Analysis: Settlement
 Author: Christopher Cook
 Company: Reitz & Jens, Inc
 Date Created: 10/17/2012, 11:48:36 AM
 Stress Computation Method: Boussinesq
 Use average properties to calculate layered stresses
 Groundwater method: Water Table
 Water Unit Weight: 0.0624 kips/ft³
 Depth to water table: 1 [ft]

Stage Settings

| Stage # | Name |
|---------|---------|
| 1 | Stage 1 |

Results

Time taken to compute: 0 seconds

Stage: Stage 1

| Data Type | Minimum | Maximum |
|------------------------------------|-------------|-----------|
| Total Settlement [in] | 0 | 24.8356 |
| Consolidation Settlement [in] | 0 | 12.1942 |
| Immediate Settlement [in] | 0 | 12.6414 |
| Loading Stress [ksf] | 0 | 10.2043 |
| Effective Stress [ksf] | 0 | 16.5846 |
| Total Stress [ksf] | 0 | 23.0742 |
| Total Strain | 3.9992e-008 | 0.0983004 |
| Pore Water Pressure [ksf] | 0 | 6.4896 |
| Degree of Consolidation [%] | 0 | 100 |
| Pre-consolidation Stress [ksf] | 0.788336 | 16.5514 |
| Over-consolidation Ratio | 1 | 80.6776 |
| Void Ratio | 0 | 0.862 |
| Hydroconsolidation Settlement [in] | 0 | 0 |

Loads

1. Polygonal Load

Load Type: Flexible
Area of Load: 183389 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1929.25 | 862.473 | 0 |
| -1332.07 | -407.189 | 0 |
| -210.328 | -424.303 | 0 |
| -270.312 | -363.597 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -1870.41 | 874.203 | 2.9 |
| -1852.31 | 1508.1 | 2.9 |
| -1908.21 | 1557.97 | 0 |

2. Polygonal Load

Load Type: Flexible
Area of Load: 234768 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -221.212 | 1808.9 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -210.328 | -424.303 | 0 |
| -162.623 | 1880.73 | 0 |
| -1908.21 | 1557.97 | 0 |

3. Polygonal Load

Load Type: Flexible
Area of Load: 156632 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1870.41 | 874.203 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -317.264 | -315.23 | 5 |
| -1259.26 | -297.655 | 5 |
| -1809.13 | 885.67 | 5 |
| -1806.79 | 1469.02 | 5 |
| -1852.31 | 1508.1 | 2.9 |

4. Polygonal Load

Load Type: Flexible
Area of Load: 171981 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -1806.79 | 1469.02 | 5 |
| -267.217 | 1755.15 | 5 |
| -317.264 | -315.23 | 5 |
| -270.312 | -363.597 | 2.9 |
| -221.212 | 1808.9 | 2.9 |

5. Polygonal Load

Load Type: Flexible
Area of Load: 244557 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -102.643 | -2757.4 | 0 |
| 1076.16 | -2794.88 | 0 |
| 1109.25 | -1637.87 | 0 |
| 3035.41 | -1668.34 | 0 |
| 2874.5 | -1608.34 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 1016.65 | -2734.4 | 2.9 |
| -39.0646 | -2705.7 | 2.9 |

6. Polygonal Load

Load Type: Flexible
Area of Load: 433982 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0604 | -2705.58 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 3035.41 | -1668.34 | 0 |
| 35.4746 | 897.295 | 0 |
| -102.643 | -2757.4 | 0 |

7. Polygonal Load

Load Type: Flexible
Area of Load: 451309 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| 27.8223 | -2642.81 | 5 |
| 153.042 | 647.667 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2874.5 | -1608.34 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| -39.0604 | -2705.58 | 2.9 |

8. Polygonal Load

Load Type: Flexible
Area of Load: 238713 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0644 | -2705.7 | 2.9 |
| 1018.23 | -2734.44 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 2690.18 | -1545.21 | 5 |
| 989.752 | -1516.32 | 5 |
| 956.638 | -2672.65 | 5 |
| 27.8223 | -2642.81 | 5 |

9. Polygonal Load

Load Type: Flexible
Area of Load: 567821 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1637.57 | 1323.75 | 10.2 |
| -447.535 | 1544.49 | 10.2 |
| -485.349 | -142.076 | 10.2 |
| -317.264 | -315.23 | 10.2 |
| -267.217 | 1755.15 | 5 |
| -1806.56 | 1468.98 | 5 |

10. Polygonal Load

Load Type: Flexible
Area of Load: 1.5903e+006 ft²

Load: 10.2 ksf
Depth: 0 ft
Installation Stage: Stage 1

Coordinates

| X [ft] | Y [ft] |
|----------|----------|
| -1649.21 | 915.592 |
| -1153.62 | -131.529 |
| -485.349 | -142.076 |
| -447.535 | 1544.49 |
| -1637.57 | 1323.75 |

11. Polygonal Load

Load Type: Flexible
Area of Load: 417396 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -485.349 | -142.076 | 10.2 |
| -1153.62 | -131.529 | 10.2 |
| -1649.21 | 915.592 | 10.2 |
| -1637.57 | 1323.75 | 10.2 |
| -1806.56 | 1468.98 | 5 |
| -1809.13 | 885.67 | 5 |
| -1259.26 | -297.655 | 5 |
| -317.264 | -315.23 | 5 |

12. Polygonal Load

Load Type: Flexible
Area of Load: 941302 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 188.83 | -2491.7 | 10.2 |
| 293.799 | 364.216 | 10.2 |
| 2201.69 | -1376.73 | 10.2 |
| 2690.18 | -1545.21 | 5 |
| 153.042 | 647.667 | 5 |
| 27.7015 | -2645.99 | 5 |

13. Polygonal Load

Load Type: Flexible
Area of Load: 551990 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 952.602 | -2672.52 | 5 |
| 989.748 | -1516.48 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2201.69 | -1376.73 | 10.2 |
| 832.524 | -1353.16 | 10.2 |
| 802.744 | -2507.54 | 10.2 |
| 188.83 | -2491.7 | 10.2 |
| 27.7015 | -2645.99 | 5 |

14. Polygonal Load

Load Type: Flexible

Area of Load: 2.38333e+006 ft²

Depth: 0 ft


Installation Stage: Stage 1

Coordinates and Load






| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 832.524 | -1353.16 | 10.2 |
| 2201.69 | -1376.73 | 10.2 |
| 293.799 | 364.216 | 10.2 |
| 188.83 | -2491.7 | 10.2 |
| 802.744 | -2507.54 | 10.2 |

Soil Layers

| Layer # | Type | Thickness [ft] | Depth [ft] |
|---------|---------------|----------------|------------|
| 1 | CLAY | 12 | 0 |
| 2 | SILT & SAND | 8 | 12 |
| 3 | SAND | 15 | 20 |
| 4 | SAND & GRAVEL | 42 | 35 |
| 5 | SAND (2) | 28 | 77 |



Soil Properties

| Property | CLAY | SILT & SAND | SAND | SAND & GRAVEL | SAND (2) |
|---|---|---|---|---|---|
| Color |  |  |  |  |  |
| Unit Weight [kips/ft ³] | 0.118 | 0.12 | 0.122 | 0.124 | 0.125 |
| Saturated Unit Weight [kips/ft ³] | 0.118 | 0.12 | 0.122 | 0.124 | 0.125 |
| Immediate Settlement | Disabled | Enabled | Enabled | Enabled | Enabled |
| Es [ksf] | | 200 | 1100 | 1000 | 1200 |
| Es bottom [ksf] | | 500 | | | |
| Esur [ksf] | | 200 | 1100 | 1000 | 1200 |
| Esur bottom [ksf] | | 500 | | | |
| Primary Consolidation | Enabled | Disabled | Disabled | Disabled | Disabled |
| Material Type | Non-Linear | | | | |
| Cc | 0.32 | | | | |
| Cr | 0.04 | | | | |
| e0 | 0.862 | | | | |
| Pc [ksf] | 4.76 | | | | |
| OCR | | 1 | 1 | 1 | 1 |
| Secondary Consolidation | Standard | Disabled | Disabled | Disabled | Disabled |
| Cae/Ca | 0.004 | | | | |
| Car/Care | 0.004 | | | | |

Query Lines

| Line # | Start Location | End Location | Horizontal Divisions | Vertical Divisions |
|--------|-------------------|------------------|----------------------|--------------------|
| 1 | -119.939, -437.96 | 1670.82, -437.96 | 100 | 101 |

Settle3D Analysis Information

Labadie UWL

Project Settings

Document Name: CIRCLE 50.s3z
 Project Title: Labadie UWL
 Analysis: Settlement
 Author: Christopher Cook
 Company: Reitz & Jens, Inc
 Date Created: 10/17/2012, 11:48:36 AM
 Stress Computation Method: Boussinesq
 Use average properties to calculate layered stresses
 Groundwater method: Water Table
 Water Unit Weight: 0.0624 kips/ft³
 Depth to water table: 1 [ft]

Stage Settings

| Stage # | Name |
|---------|---------|
| 1 | Stage 1 |

Results

Time taken to compute: 0 seconds

Stage: Stage 1

| Data Type | Minimum | Maximum |
|------------------------------------|-------------|-----------|
| Total Settlement [in] | 0 | 24.747 |
| Consolidation Settlement [in] | 0 | 12.1942 |
| Immediate Settlement [in] | 0 | 12.5528 |
| Loading Stress [ksf] | 0 | 10.2043 |
| Effective Stress [ksf] | 0 | 16.5806 |
| Total Stress [ksf] | 0 | 23.0702 |
| Total Strain | 3.9992e-008 | 0.0983004 |
| Pore Water Pressure [ksf] | 0 | 6.4896 |
| Degree of Consolidation [%] | 0 | 100 |
| Pre-consolidation Stress [ksf] | 0.788336 | 16.5474 |
| Over-consolidation Ratio | 1 | 80.6776 |
| Void Ratio | 0 | 0.862 |
| Hydroconsolidation Settlement [in] | 0 | 0 |

Loads

1. Polygonal Load

Load Type: Flexible
Area of Load: 183389 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1929.25 | 862.473 | 0 |
| -1332.07 | -407.189 | 0 |
| -210.328 | -424.303 | 0 |
| -270.312 | -363.597 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -1870.41 | 874.203 | 2.9 |
| -1852.31 | 1508.1 | 2.9 |
| -1908.21 | 1557.97 | 0 |

2. Polygonal Load

Load Type: Flexible
Area of Load: 234768 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -221.212 | 1808.9 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -210.328 | -424.303 | 0 |
| -162.623 | 1880.73 | 0 |
| -1908.21 | 1557.97 | 0 |

3. Polygonal Load

Load Type: Flexible
Area of Load: 156632 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1870.41 | 874.203 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -317.264 | -315.23 | 5 |
| -1259.26 | -297.655 | 5 |
| -1809.13 | 885.67 | 5 |
| -1806.79 | 1469.02 | 5 |
| -1852.31 | 1508.1 | 2.9 |

4. Polygonal Load

Load Type: Flexible
Area of Load: 171981 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -1806.79 | 1469.02 | 5 |
| -267.217 | 1755.15 | 5 |
| -317.264 | -315.23 | 5 |
| -270.312 | -363.597 | 2.9 |
| -221.212 | 1808.9 | 2.9 |

5. Polygonal Load

Load Type: Flexible
Area of Load: 244557 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -102.643 | -2757.4 | 0 |
| 1076.16 | -2794.88 | 0 |
| 1109.25 | -1637.87 | 0 |
| 3035.41 | -1668.34 | 0 |
| 2874.5 | -1608.34 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 1016.65 | -2734.4 | 2.9 |
| -39.0646 | -2705.7 | 2.9 |

6. Polygonal Load

Load Type: Flexible
Area of Load: 433982 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0604 | -2705.58 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 3035.41 | -1668.34 | 0 |
| 35.4746 | 897.295 | 0 |
| -102.643 | -2757.4 | 0 |

7. Polygonal Load

Load Type: Flexible
Area of Load: 451309 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| 27.8223 | -2642.81 | 5 |
| 153.042 | 647.667 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2874.5 | -1608.34 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| -39.0604 | -2705.58 | 2.9 |

8. Polygonal Load

Load Type: Flexible
Area of Load: 238713 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0644 | -2705.7 | 2.9 |
| 1018.23 | -2734.44 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 2690.18 | -1545.21 | 5 |
| 989.752 | -1516.32 | 5 |
| 956.638 | -2672.65 | 5 |
| 27.8223 | -2642.81 | 5 |

9. Polygonal Load

Load Type: Flexible
Area of Load: 567821 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1637.57 | 1323.75 | 10.2 |
| -447.535 | 1544.49 | 10.2 |
| -485.349 | -142.076 | 10.2 |
| -317.264 | -315.23 | 10.2 |
| -267.217 | 1755.15 | 5 |
| -1806.56 | 1468.98 | 5 |

10. Polygonal Load

Load Type: Flexible
Area of Load: 1.5903e+006 ft²

Load: 10.2 ksf
Depth: 0 ft
Installation Stage: Stage 1

Coordinates

| X [ft] | Y [ft] |
|----------|----------|
| -1649.21 | 915.592 |
| -1153.62 | -131.529 |
| -485.349 | -142.076 |
| -447.535 | 1544.49 |
| -1637.57 | 1323.75 |

11. Polygonal Load

Load Type: Flexible
Area of Load: 417396 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -485.349 | -142.076 | 10.2 |
| -1153.62 | -131.529 | 10.2 |
| -1649.21 | 915.592 | 10.2 |
| -1637.57 | 1323.75 | 10.2 |
| -1806.56 | 1468.98 | 5 |
| -1809.13 | 885.67 | 5 |
| -1259.26 | -297.655 | 5 |
| -317.264 | -315.23 | 5 |

12. Polygonal Load

Load Type: Flexible
Area of Load: 941302 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 188.83 | -2491.7 | 10.2 |
| 293.799 | 364.216 | 10.2 |
| 2201.69 | -1376.73 | 10.2 |
| 2690.18 | -1545.21 | 5 |
| 153.042 | 647.667 | 5 |
| 27.7015 | -2645.99 | 5 |

13. Polygonal Load

Load Type: Flexible
Area of Load: 551990 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 952.602 | -2672.52 | 5 |
| 989.748 | -1516.48 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2201.69 | -1376.73 | 10.2 |
| 832.524 | -1353.16 | 10.2 |
| 802.744 | -2507.54 | 10.2 |
| 188.83 | -2491.7 | 10.2 |
| 27.7015 | -2645.99 | 5 |

14. Polygonal Load

Load Type: Flexible

Area of Load: 2.38333e+006 ft²

Depth: 0 ft


Installation Stage: Stage 1

Coordinates and Load






| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 832.524 | -1353.16 | 10.2 |
| 2201.69 | -1376.73 | 10.2 |
| 293.799 | 364.216 | 10.2 |
| 188.83 | -2491.7 | 10.2 |
| 802.744 | -2507.54 | 10.2 |

Soil Layers

| Layer # | Type | Thickness [ft] | Depth [ft] |
|---------|---------------|----------------|------------|
| 1 | CLAY | 12 | 0 |
| 2 | SILT & SAND | 8 | 12 |
| 3 | SAND | 17 | 20 |
| 4 | SAND & GRAVEL | 40 | 37 |
| 5 | SAND (2) | 28 | 77 |



Soil Properties

| Property | CLAY | SILT & SAND | SAND | SAND & GRAVEL | SAND (2) |
|---|---|---|---|---|---|
| Color |  |  |  |  |  |
| Unit Weight [kips/ft ³] | 0.118 | 0.12 | 0.122 | 0.124 | 0.125 |
| Saturated Unit Weight [kips/ft ³] | 0.118 | 0.12 | 0.122 | 0.124 | 0.125 |
| Immediate Settlement | Disabled | Enabled | Enabled | Enabled | Enabled |
| Es [ksf] | | 300 | 900 | 1000 | 1200 |
| Es bottom [ksf] | | 500 | | | |
| Esur [ksf] | | 300 | 900 | 1000 | 1200 |
| Esur bottom [ksf] | | 500 | | | |
| Primary Consolidation | Enabled | Disabled | Disabled | Disabled | Disabled |
| Material Type | Non-Linear | | | | |
| Cc | 0.32 | | | | |
| Cr | 0.04 | | | | |
| e0 | 0.862 | | | | |
| Pc [ksf] | 4.76 | | | | |
| OCR | | 1 | 1 | 1 | 1 |
| Secondary Consolidation | Standard | Disabled | Disabled | Disabled | Disabled |
| Cae/Ca | 0.004 | | | | |
| Car/Care | 0.004 | | | | |

Query Lines

| Line # | Start Location | End Location | Horizontal Divisions | Vertical Divisions |
|--------|-------------------|------------------|----------------------|--------------------|
| 1 | -119.939, -437.96 | 1670.82, -437.96 | 100 | 101 |

Settle3D Analysis Information

Project Settings

Document Name: circle 12 Labadie.s3z
Date Created: 3/15/2011, 2:21:05 PM
Stress Computation Method: Boussinesq
Include buoyancy effect when material settles below water table
Use average properties to calculate layered stresses
Groundwater method: Water Table
Water Unit Weight: 0.0624 kips/ft³
Depth to water table: 0 [ft]

Stage Settings

| Stage # | Name |
|---------|---------|
| 1 | Stage 1 |

Results

Time taken to compute: 0 seconds

Stage: Stage 1

| Data Type | Minimum | Maximum |
|------------------------------------|--------------|------------|
| Total Settlement [in] | 0 | 0.167998 |
| Consolidation Settlement [in] | 0 | 0.0707617 |
| Immediate Settlement [in] | 0 | 0.142156 |
| Loading Stress [ksf] | 0 | 0.531582 |
| Effective Stress [ksf] | 0 | 6.69012 |
| Total Stress [ksf] | 0 | 13.1166 |
| Total Strain | 4.27224e-009 | 0.00181831 |
| Pore Water Pressure [ksf] | 0 | 6.42712 |
| Degree of Consolidation [%] | 0 | 100 |
| Pre-consolidation Stress [ksf] | 1.13095 | 6.68765 |
| Over-consolidation Ratio | 1 | 171.223 |
| Void Ratio | 0 | 0.862 |
| Hydroconsolidation Settlement [in] | 0 | 0 |

Loads

1. Polygonal Load

Load Type: Flexible
Area of Load: 183389 ft²

Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1929.25 | 862.473 | 0 |
| -1332.07 | -407.189 | 0 |
| -210.328 | -424.303 | 0 |
| -270.312 | -363.597 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -1870.41 | 874.203 | 2.9 |
| -1852.31 | 1508.1 | 2.9 |
| -1908.21 | 1557.97 | 0 |

2. Polygonal Load

Load Type: Flexible
Area of Load: 234768 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -221.212 | 1808.9 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -210.328 | -424.303 | 0 |
| -162.623 | 1880.73 | 0 |
| -1908.21 | 1557.97 | 0 |

3. Polygonal Load

Load Type: Flexible
Area of Load: 156632 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1870.41 | 874.203 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -317.264 | -315.23 | 5 |
| -1259.26 | -297.655 | 5 |
| -1809.13 | 885.67 | 5 |
| -1806.79 | 1469.02 | 5 |
| -1852.31 | 1508.1 | 2.9 |

4. Polygonal Load

Load Type: Flexible

Area of Load: 171981 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -1806.79 | 1469.02 | 5 |
| -267.217 | 1755.15 | 5 |
| -317.264 | -315.23 | 5 |
| -270.312 | -363.597 | 2.9 |
| -221.212 | 1808.9 | 2.9 |

5. Polygonal Load

Load Type: Flexible
Area of Load: 244557 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -102.643 | -2757.4 | 0 |
| 1076.16 | -2794.88 | 0 |
| 1109.25 | -1637.87 | 0 |
| 3035.41 | -1668.34 | 0 |
| 2874.5 | -1608.34 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 1016.65 | -2734.4 | 2.9 |
| -39.0646 | -2705.7 | 2.9 |

6. Polygonal Load

Load Type: Flexible
Area of Load: 433982 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0604 | -2705.58 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 3035.41 | -1668.34 | 0 |
| 35.4746 | 897.295 | 0 |
| -102.643 | -2757.4 | 0 |

7. Polygonal Load

Load Type: Flexible
Area of Load: 451309 ft²

Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| 27.8223 | -2642.81 | 5 |
| 153.042 | 647.667 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2874.5 | -1608.34 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| -39.0604 | -2705.58 | 2.9 |

8. Polygonal Load

Load Type: Flexible
Area of Load: 238713 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0644 | -2705.7 | 2.9 |
| 1018.23 | -2734.44 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 2690.18 | -1545.21 | 5 |
| 989.752 | -1516.32 | 5 |
| 956.638 | -2672.65 | 5 |
| 27.8223 | -2642.81 | 5 |

9. Polygonal Load

Load Type: Flexible
Area of Load: 567821 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1637.57 | 1323.75 | 10 |
| -447.535 | 1544.49 | 10 |
| -485.349 | -142.076 | 10 |
| -317.264 | -315.23 | 5 |
| -267.217 | 1755.15 | 5 |
| -1806.56 | 1468.98 | 5 |

10. Polygonal Load

Load Type: Flexible
Area of Load: 1.5903e+006 ft²
Depth: 0 ft

Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1649.21 | 915.592 | 10.2 |
| -1153.62 | -131.529 | 10.2 |
| -485.349 | -142.076 | 10.2 |
| -447.535 | 1544.49 | 10.2 |
| -1637.57 | 1323.75 | 10.2 |

11. Polygonal Load

Load Type: Flexible
Area of Load: 417396 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -485.349 | -142.076 | 10 |
| -1153.62 | -131.529 | 10 |
| -1649.21 | 915.592 | 10 |
| -1637.57 | 1323.75 | 10 |
| -1806.56 | 1468.98 | 5 |
| -1809.13 | 885.67 | 5 |
| -1259.26 | -297.655 | 5 |
| -317.264 | -315.23 | 5 |

12. Polygonal Load

Load Type: Flexible
Area of Load: 941302 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 188.83 | -2491.7 | 10 |
| 293.799 | 364.216 | 10 |
| 2201.69 | -1376.73 | 10 |
| 2690.18 | -1545.21 | 5 |
| 153.042 | 647.667 | 5 |
| 27.7015 | -2645.99 | 5 |

13. Polygonal Load

Load Type: Flexible
Area of Load: 551990 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 952.602 | -2672.52 | 5 |
| 989.748 | -1516.48 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2201.69 | -1376.73 | 10 |
| 832.524 | -1353.16 | 10 |
| 802.744 | -2507.54 | 10 |
| 188.83 | -2491.7 | 10 |
| 27.7015 | -2645.99 | 5 |

14. Polygonal Load

Load Type: Flexible

Area of Load: 2.38333e+006 ft²

Depth: 0 ft


Installation Stage: Stage 1

Coordinates and Load







| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 832.524 | -1353.16 | 10.2 |
| 2201.69 | -1376.73 | 10.2 |
| 293.799 | 364.216 | 10.2 |
| 188.83 | -2491.7 | 10.2 |
| 802.744 | -2507.54 | 10.2 |

Soil Layers

| Layer # | Type | Thickness [ft] | Depth [ft] |
|---------|---------------|----------------|------------|
| 1 | CLAY | 10 | 0 |
| 2 | SILT | 10 | 10 |
| 3 | SAND | 5 | 20 |
| 4 | SILT & SAND | 6 | 25 |
| 5 | LOWER SAND | 4 | 31 |
| 6 | SAND & GRAVEL | 68 | 35 |



Soil Properties

| Property | CLAY | SILT | SAND | SILT & SAND | LOWER SAND | SAND & GRAVEL |
|---|---|---|---|---|---|---|
| Color |  |  |  |  |  |  |
| Unit Weight [kips/ft ³] | 0.118 | 0.117 | 0.119 | 0.12 | 0.122 | 0.124 |
| Saturated Unit Weight [kips/ft ³] | 0.118 | 0.117 | 0.119 | 0.12 | 0.122 | 0.124 |
| Immediate Settlement | Disabled | Enabled | Enabled | Enabled | Enabled | Enabled |
| Es [ksf] | | 200 | 800 | 600 | 900 | 1400 |
| Es bottom [ksf] | | 500 | | | | |
| Esur [ksf] | | 200 | 800 | 600 | 900 | 1400 |
| Esur bottom [ksf] | | 500 | | | | |
| Primary Consolidation | Enabled | Disabled | Disabled | Disabled | Disabled | Disabled |
| Material Type | Non-Linear | | | | | |
| Cc | 0.32 | | | | | |
| Cr | 0.04 | | | | | |
| e0 | 0.862 | | | | | |
| Pc [ksf] | 4.76 | 4.52 | | | | |
| OCR | | | 1 | 1 | 1 | 1 |
| Secondary Consolidation | Standard | Disabled | Disabled | Disabled | Disabled | Disabled |
| Cae/Ca | 0.004 | | | | | |
| Car/Care | 0.004 | | | | | |

Query Lines

| Line # | Start Location | End Location | Horizontal Divisions | Vertical Divisions |
|--------|----------------|--------------|----------------------|--------------------|
| 1 | -37, 1887 | -188, -1959 | 100 | Auto: 61 |

Settle3D Analysis Information

Project Settings

Document Name: circle 11 Labadie.s3z
Date Created: 3/15/2011, 2:21:05 PM
Stress Computation Method: Boussinesq
Include buoyancy effect when material settles below water table
Use average properties to calculate layered stresses
Groundwater method: Water Table
Water Unit Weight: 0.0624 kips/ft³
Depth to water table: 0 [ft]

Stage Settings

| Stage # | Name |
|---------|---------|
| 1 | Stage 1 |

Results

Time taken to compute: 0 seconds

Stage: Stage 1

| Data Type | Minimum | Maximum |
|------------------------------------|---------|------------|
| Total Settlement [in] | 0 | 0.198016 |
| Consolidation Settlement [in] | 0 | 0.0968068 |
| Immediate Settlement [in] | 0 | 0.148182 |
| Loading Stress [ksf] | 0 | 0.531582 |
| Effective Stress [ksf] | 0 | 6.66916 |
| Total Stress [ksf] | 0 | 13.0956 |
| Total Strain | 0 | 0.00603323 |
| Pore Water Pressure [ksf] | 0 | 6.42712 |
| Degree of Consolidation [%] | 0 | 100 |
| Pre-consolidation Stress [ksf] | 1.1603 | 6.66669 |
| Over-consolidation Ratio | 1 | 713.429 |
| Void Ratio | 0 | 0.862 |
| Hydroconsolidation Settlement [in] | 0 | 0 |

Loads

1. Polygonal Load

Load Type: Flexible
Area of Load: 183389 ft²

Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1929.25 | 862.473 | 0 |
| -1332.07 | -407.189 | 0 |
| -210.328 | -424.303 | 0 |
| -270.312 | -363.597 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -1870.41 | 874.203 | 2.9 |
| -1852.31 | 1508.1 | 2.9 |
| -1908.21 | 1557.97 | 0 |

2. Polygonal Load

Load Type: Flexible
Area of Load: 234768 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -221.212 | 1808.9 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -210.328 | -424.303 | 0 |
| -162.623 | 1880.73 | 0 |
| -1908.21 | 1557.97 | 0 |

3. Polygonal Load

Load Type: Flexible
Area of Load: 156632 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1870.41 | 874.203 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -317.264 | -315.23 | 5 |
| -1259.26 | -297.655 | 5 |
| -1809.13 | 885.67 | 5 |
| -1806.79 | 1469.02 | 5 |
| -1852.31 | 1508.1 | 2.9 |

4. Polygonal Load

Load Type: Flexible

Area of Load: 171981 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -1806.79 | 1469.02 | 5 |
| -267.217 | 1755.15 | 5 |
| -317.264 | -315.23 | 5 |
| -270.312 | -363.597 | 2.9 |
| -221.212 | 1808.9 | 2.9 |

5. Polygonal Load

Load Type: Flexible
Area of Load: 244557 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -102.643 | -2757.4 | 0 |
| 1076.16 | -2794.88 | 0 |
| 1109.25 | -1637.87 | 0 |
| 3035.41 | -1668.34 | 0 |
| 2874.5 | -1608.34 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 1016.65 | -2734.4 | 2.9 |
| -39.0646 | -2705.7 | 2.9 |

6. Polygonal Load

Load Type: Flexible
Area of Load: 433982 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0604 | -2705.58 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 3035.41 | -1668.34 | 0 |
| 35.4746 | 897.295 | 0 |
| -102.643 | -2757.4 | 0 |

7. Polygonal Load

Load Type: Flexible
Area of Load: 451309 ft²

Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| 27.8223 | -2642.81 | 5 |
| 153.042 | 647.667 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2874.5 | -1608.34 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| -39.0604 | -2705.58 | 2.9 |

8. Polygonal Load

Load Type: Flexible
Area of Load: 238713 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0644 | -2705.7 | 2.9 |
| 1018.23 | -2734.44 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 2690.18 | -1545.21 | 5 |
| 989.752 | -1516.32 | 5 |
| 956.638 | -2672.65 | 5 |
| 27.8223 | -2642.81 | 5 |

9. Polygonal Load

Load Type: Flexible
Area of Load: 567821 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1637.57 | 1323.75 | 10 |
| -447.535 | 1544.49 | 10 |
| -485.349 | -142.076 | 10 |
| -317.264 | -315.23 | 5 |
| -267.217 | 1755.15 | 5 |
| -1806.56 | 1468.98 | 5 |

10. Polygonal Load

Load Type: Flexible
Area of Load: 1.5903e+006 ft²
Depth: 0 ft

Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1649.21 | 915.592 | 10.2 |
| -1153.62 | -131.529 | 10.2 |
| -485.349 | -142.076 | 10.2 |
| -447.535 | 1544.49 | 10.2 |
| -1637.57 | 1323.75 | 10.2 |

11. Polygonal Load

Load Type: Flexible

Area of Load: 417396 ft²

Depth: 0 ft

Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -485.349 | -142.076 | 10 |
| -1153.62 | -131.529 | 10 |
| -1649.21 | 915.592 | 10 |
| -1637.57 | 1323.75 | 10 |
| -1806.56 | 1468.98 | 5 |
| -1809.13 | 885.67 | 5 |
| -1259.26 | -297.655 | 5 |
| -317.264 | -315.23 | 5 |

12. Polygonal Load

Load Type: Flexible

Area of Load: 941302 ft²

Depth: 0 ft

Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 188.83 | -2491.7 | 10 |
| 293.799 | 364.216 | 10 |
| 2201.69 | -1376.73 | 10 |
| 2690.18 | -1545.21 | 5 |
| 153.042 | 647.667 | 5 |
| 27.7015 | -2645.99 | 5 |

13. Polygonal Load

Load Type: Flexible

Area of Load: 551990 ft²

Depth: 0 ft

Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 952.602 | -2672.52 | 5 |
| 989.748 | -1516.48 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2201.69 | -1376.73 | 10 |
| 832.524 | -1353.16 | 10 |
| 802.744 | -2507.54 | 10 |
| 188.83 | -2491.7 | 10 |
| 27.7015 | -2645.99 | 5 |

14. Polygonal Load

Load Type: Flexible

Area of Load: 2.38333e+006 ft²

Depth: 0 ft


Installation Stage: Stage 1

Coordinates and Load






| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 832.524 | -1353.16 | 10.2 |
| 2201.69 | -1376.73 | 10.2 |
| 293.799 | 364.216 | 10.2 |
| 188.83 | -2491.7 | 10.2 |
| 802.744 | -2507.54 | 10.2 |

Soil Layers

| Layer # | Type | Thickness [ft] | Depth [ft] |
|---------|---------------|----------------|------------|
| 1 | CLAY | 12 | 0 |
| 2 | SILT | 8 | 12 |
| 3 | SILT & SAND | 10 | 20 |
| 4 | CLAY & SILT | 5 | 30 |
| 5 | SAND & GRAVEL | 68 | 35 |



Soil Properties

| Property | CLAY | SILT | SILT & SAND | CLAY & SILT | SAND & GRAVEL |
|---|---|---|---|---|---|
| Color |  |  |  |  |  |
| Unit Weight [kips/ft ³] | 0.118 | 0.117 | 0.118 | 0.12 | 0.124 |
| Saturated Unit Weight [kips/ft ³] | 0.118 | 0.117 | 0.118 | 0.12 | 0.124 |
| Immediate Settlement | Disabled | Enabled | Enabled | Enabled | Enabled |
| Es [ksf] | | 400 | 500 | 225 | 1400 |
| Esur [ksf] | | 400 | 500 | 225 | 1400 |
| Primary Consolidation | Enabled | Disabled | Disabled | Disabled | Disabled |
| Material Type | Non-Linear | | | | |
| Cc | 0.32 | | | | |
| Cr | 0.04 | | | | |
| e0 | 0.862 | | | | |
| Pc [ksf] | 4.76 | 4.52 | | | |
| OCR | | | 1 | 1 | 1 |
| Secondary Consolidation | Standard | Disabled | Disabled | Disabled | Disabled |
| Cae/Ca | 0.004 | | | | |
| Car/Care | 0.004 | | | | |

Query Lines

| Line # | Start Location | End Location | Horizontal Divisions | Vertical Divisions |
|--------|----------------|--------------|----------------------|--------------------|
| 1 | -37, 1887 | -188, -1959 | 100 | Auto: 59 |

Settle3D Analysis Information

Labadie UWL

Project Settings

Document Name: circle 9.s3z
Project Title: Labadie UWL
Analysis: Settlement
Author: Christopher Cook
Company: Reitz & Jens, Inc
Date Created: 10/17/2012, 11:48:36 AM
Stress Computation Method: Boussinesq
Use average properties to calculate layered stresses
Groundwater method: Water Table
Water Unit Weight: 0.0624 kips/ft³
Depth to water table: 1 [ft]

Stage Settings

| Stage # | Name |
|---------|---------|
| 1 | Stage 1 |

Loads

1. Polygonal Load

Load Type: Flexible
Area of Load: 183389 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1929.25 | 862.473 | 0 |
| -1332.07 | -407.189 | 0 |
| -210.328 | -424.303 | 0 |
| -270.312 | -363.597 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -1870.41 | 874.203 | 2.9 |
| -1852.31 | 1508.1 | 2.9 |
| -1908.21 | 1557.97 | 0 |

2. Polygonal Load

Load Type: Flexible
Area of Load: 234768 ft²
Depth: 0 ft

Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -221.212 | 1808.9 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -210.328 | -424.303 | 0 |
| -162.623 | 1880.73 | 0 |
| -1908.21 | 1557.97 | 0 |

3. Polygonal Load

Load Type: Flexible

Area of Load: 156632 ft²

Depth: 0 ft

Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1870.41 | 874.203 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -317.264 | -315.23 | 5 |
| -1259.26 | -297.655 | 5 |
| -1809.13 | 885.67 | 5 |
| -1806.79 | 1469.02 | 5 |
| -1852.31 | 1508.1 | 2.9 |

4. Polygonal Load

Load Type: Flexible

Area of Load: 171981 ft²

Depth: 0 ft

Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -1806.79 | 1469.02 | 5 |
| -267.217 | 1755.15 | 5 |
| -317.264 | -315.23 | 5 |
| -270.312 | -363.597 | 2.9 |
| -221.212 | 1808.9 | 2.9 |

5. Polygonal Load

Load Type: Flexible

Area of Load: 244557 ft²

Depth: 0 ft

Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -102.643 | -2757.4 | 0 |
| 1076.16 | -2794.88 | 0 |
| 1109.25 | -1637.87 | 0 |
| 3035.41 | -1668.34 | 0 |
| 2874.5 | -1608.34 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 1016.65 | -2734.4 | 2.9 |
| -39.0646 | -2705.7 | 2.9 |

6. Polygonal Load

Load Type: Flexible
Area of Load: 433982 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0604 | -2705.58 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 3035.41 | -1668.34 | 0 |
| 35.4746 | 897.295 | 0 |
| -102.643 | -2757.4 | 0 |

7. Polygonal Load

Load Type: Flexible
Area of Load: 451309 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| 27.8223 | -2642.81 | 5 |
| 153.042 | 647.667 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2874.5 | -1608.34 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| -39.0604 | -2705.58 | 2.9 |

8. Polygonal Load

Load Type: Flexible
Area of Load: 238713 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|--------|--------|----------------------|
|--------|--------|----------------------|

| | | |
|----------|----------|-----|
| -39.0644 | -2705.7 | 2.9 |
| 1018.23 | -2734.44 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 2690.18 | -1545.21 | 5 |
| 989.752 | -1516.32 | 5 |
| 956.638 | -2672.65 | 5 |
| 27.8223 | -2642.81 | 5 |

9. Polygonal Load

Load Type: Flexible
Area of Load: 567821 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1637.57 | 1323.75 | 10.2 |
| -447.535 | 1544.49 | 10.2 |
| -485.349 | -142.076 | 10.2 |
| -317.264 | -315.23 | 10.2 |
| -267.217 | 1755.15 | 5 |
| -1806.56 | 1468.98 | 5 |

10. Polygonal Load

Load Type: Flexible
Area of Load: 1.5903e+006 ft²
Load: 10.2 ksf
Depth: 0 ft
Installation Stage: Stage 1

Coordinates

| X [ft] | Y [ft] |
|----------|----------|
| -1649.21 | 915.592 |
| -1153.62 | -131.529 |
| -485.349 | -142.076 |
| -447.535 | 1544.49 |
| -1637.57 | 1323.75 |

11. Polygonal Load

Load Type: Flexible
Area of Load: 417396 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -485.349 | -142.076 | 10.2 |
| -1153.62 | -131.529 | 10.2 |

| | | |
|----------|----------|------|
| -1649.21 | 915.592 | 10.2 |
| -1637.57 | 1323.75 | 10.2 |
| -1806.56 | 1468.98 | 5 |
| -1809.13 | 885.67 | 5 |
| -1259.26 | -297.655 | 5 |
| -317.264 | -315.23 | 5 |

12. Polygonal Load

Load Type: Flexible
Area of Load: 941302 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 188.83 | -2491.7 | 10.2 |
| 293.799 | 364.216 | 10.2 |
| 2201.69 | -1376.73 | 10.2 |
| 2690.18 | -1545.21 | 5 |
| 153.042 | 647.667 | 5 |
| 27.7015 | -2645.99 | 5 |

13. Polygonal Load

Load Type: Flexible
Area of Load: 551990 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 952.602 | -2672.52 | 5 |
| 989.748 | -1516.48 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2201.69 | -1376.73 | 10.2 |
| 832.524 | -1353.16 | 10.2 |
| 802.744 | -2507.54 | 10.2 |
| 188.83 | -2491.7 | 10.2 |
| 27.7015 | -2645.99 | 5 |

14. Polygonal Load

Load Type: Flexible
Area of Load: 2.38333e+006 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 832.524 | -1353.16 | 10.2 |
| 2201.69 | -1376.73 | 10.2 |

| | | |
|---------|----------|------|
| 293.799 | 364.216 | 10.2 |
| 188.83 | -2491.7 | 10.2 |
| 802.744 | -2507.54 | 10.2 |

15. Polygonal Load

Load Type: Flexible
Area of Load: 6368.13 ft²
Load: 2.2 ksf
Depth: 0 ft
Installation Stage: Stage 1

Coordinates

| X [ft] | Y [ft] |
|----------|---------|
| -189.163 | 598.37 |
| 24.1777 | 598.37 |
| 25.3044 | 628.184 |
| -188.546 | 628.184 |

16. Polygonal Load

Load Type: Flexible
Area of Load: 36129.2 ft²
Depth: 0 ft
Installation Stage: Stage 1


Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|---------|----------------------|
| -263.883 | 598.37 | 0 |
| -190.3 | 543.421 | 0 |
| -189.163 | 598.37 | 2.2 |
| -188.546 | 628.184 | 2.2 |
| 25.3044 | 628.184 | 2.2 |
| 24.1777 | 598.37 | 2.2 |
| -189.163 | 598.37 | 2.2 |
| -190.3 | 543.421 | 0 |
| 22.101 | 543.421 | 0 |
| 100.385 | 598.37 | 0 |
| 100.385 | 628.184 | 0 |
| 27.3659 | 682.733 | 0 |
| -187.417 | 682.733 | 0 |
| -263.883 | 628.184 | 0 |

Soil Layers

| Layer # | Type | Thickness [ft] | Depth [ft] |
|---------|-------------|----------------|------------|
| 1 | CLAY | 7 | 0 |
| 2 | SILT | 9 | 7 |
| 3 | SILT & SAND | 6 | 16 |
| 4 | SAND | 13 | 22 |

| | | | |
|---|---------------|----|----|
| 5 | LOWER SAND | 10 | 35 |
| 6 | SAND & GRAVEL | 58 | 45 |



Soil Properties

| Property | CLAY | SILT | SILT & SAND | SAND | SAND & GRAVEL | LOWER SAND |
|---|------------|----------|-------------|----------|---------------|------------|
| Color | | | | | | |
| Unit Weight [kips/ft ³] | 0.113 | 0.117 | 0.12 | 0.122 | 0.124 | 0.124 |
| Saturated Unit Weight [kips/ft ³] | 0.113 | 0.117 | 0.12 | 0.122 | 0.124 | 0.124 |
| Immediate Settlement | Disabled | Enabled | Enabled | Enabled | Enabled | Enabled |
| Es [ksf] | | 300 | 900 | 1100 | 1400 | 1300 |
| Esur [ksf] | | 300 | 900 | 1100 | 1400 | 1300 |
| Primary Consolidation | Enabled | Disabled | Disabled | Disabled | Disabled | Disabled |
| Material Type | Non-Linear | | | | | |
| Cc | 0.3 | | | | | |
| Cr | 0.05 | | | | | |
| e0 | 0.917 | | | | | |
| Pc [ksf] | 4.52 | | | | | |
| OCR | | 1 | 1 | 1 | 1 | 1 |
| Secondary Consolidation | Standard | Disabled | Disabled | Disabled | Disabled | Disabled |
| Cae/Ca | 0.005 | | | | | |
| Car/Care | 0.005 | | | | | |

Query Lines

| Line # | Start Location | End Location | Horizontal Divisions | Vertical Divisions |
|--------|----------------|--------------|----------------------|--------------------|
| 1 | -37, 1887 | -188, -1959 | 100 | 100 |

Settle3D Analysis Information

Labadie UWL

Project Settings

Document Name: CIRCLE 48.s3z
 Project Title: Labadie UWL
 Analysis: Settlement
 Author: Christopher Cook
 Company: Reitz & Jens, Inc
 Date Created: 10/17/2012, 11:48:36 AM
 Stress Computation Method: Boussinesq
 Use average properties to calculate layered stresses
 Groundwater method: Water Table
 Water Unit Weight: 0.0624 kips/ft³
 Depth to water table: 1 [ft]

Stage Settings

| Stage # | Name |
|---------|---------|
| 1 | Stage 1 |

Results

Time taken to compute: 0 seconds

Stage: Stage 1

| Data Type | Minimum | Maximum |
|------------------------------------|--------------|-----------|
| Total Settlement [in] | 0 | 4.28082 |
| Consolidation Settlement [in] | 0 | 1.93172 |
| Immediate Settlement [in] | 0 | 2.34909 |
| Loading Stress [ksf] | 0 | 2.20022 |
| Effective Stress [ksf] | 0 | 7.76966 |
| Total Stress [ksf] | 0 | 14.2593 |
| Total Strain | 2.30708e-009 | 0.0552686 |
| Pore Water Pressure [ksf] | 0 | 6.4896 |
| Degree of Consolidation [%] | 0 | 100 |
| Pre-consolidation Stress [ksf] | 0.498421 | 7.76591 |
| Over-consolidation Ratio | 1 | 806.771 |
| Void Ratio | 0 | 0.862 |
| Hydroconsolidation Settlement [in] | 0 | 0 |

Loads

1. Polygonal Load

Load Type: Flexible
Area of Load: 183389 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1929.25 | 862.473 | 0 |
| -1332.07 | -407.189 | 0 |
| -210.328 | -424.303 | 0 |
| -270.312 | -363.597 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -1870.41 | 874.203 | 2.9 |
| -1852.31 | 1508.1 | 2.9 |
| -1908.21 | 1557.97 | 0 |

2. Polygonal Load

Load Type: Flexible
Area of Load: 234768 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -221.212 | 1808.9 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -210.328 | -424.303 | 0 |
| -162.623 | 1880.73 | 0 |
| -1908.21 | 1557.97 | 0 |

3. Polygonal Load

Load Type: Flexible
Area of Load: 156632 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1870.41 | 874.203 | 2.9 |
| -1293.01 | -349.297 | 2.9 |
| -270.312 | -363.597 | 2.9 |
| -317.264 | -315.23 | 5 |
| -1259.26 | -297.655 | 5 |
| -1809.13 | 885.67 | 5 |
| -1806.79 | 1469.02 | 5 |
| -1852.31 | 1508.1 | 2.9 |

4. Polygonal Load

Load Type: Flexible
Area of Load: 171981 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1852.31 | 1508.1 | 2.9 |
| -1806.79 | 1469.02 | 5 |
| -267.217 | 1755.15 | 5 |
| -317.264 | -315.23 | 5 |
| -270.312 | -363.597 | 2.9 |
| -221.212 | 1808.9 | 2.9 |

5. Polygonal Load

Load Type: Flexible
Area of Load: 244557 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -102.643 | -2757.4 | 0 |
| 1076.16 | -2794.88 | 0 |
| 1109.25 | -1637.87 | 0 |
| 3035.41 | -1668.34 | 0 |
| 2874.5 | -1608.34 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 1016.65 | -2734.4 | 2.9 |
| -39.0646 | -2705.7 | 2.9 |

6. Polygonal Load

Load Type: Flexible
Area of Load: 433982 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0604 | -2705.58 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 3035.41 | -1668.34 | 0 |
| 35.4746 | 897.295 | 0 |
| -102.643 | -2757.4 | 0 |

7. Polygonal Load

Load Type: Flexible
Area of Load: 451309 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| 27.8223 | -2642.81 | 5 |
| 153.042 | 647.667 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2874.5 | -1608.34 | 2.9 |
| 88.9461 | 776.742 | 2.9 |
| -39.0604 | -2705.58 | 2.9 |

8. Polygonal Load

Load Type: Flexible
Area of Load: 238713 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -39.0644 | -2705.7 | 2.9 |
| 1018.23 | -2734.44 | 2.9 |
| 1048.12 | -1576.89 | 2.9 |
| 2874.5 | -1608.34 | 2.9 |
| 2690.18 | -1545.21 | 5 |
| 989.752 | -1516.32 | 5 |
| 956.638 | -2672.65 | 5 |
| 27.8223 | -2642.81 | 5 |

9. Polygonal Load

Load Type: Flexible
Area of Load: 567821 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -1637.57 | 1323.75 | 10.2 |
| -447.535 | 1544.49 | 10.2 |
| -485.349 | -142.076 | 10.2 |
| -317.264 | -315.23 | 10.2 |
| -267.217 | 1755.15 | 5 |
| -1806.56 | 1468.98 | 5 |

10. Polygonal Load

Load Type: Flexible
Area of Load: 1.5903e+006 ft²

Load: 10.2 ksf
Depth: 0 ft
Installation Stage: Stage 1

Coordinates

| X [ft] | Y [ft] |
|----------|----------|
| -1649.21 | 915.592 |
| -1153.62 | -131.529 |
| -485.349 | -142.076 |
| -447.535 | 1544.49 |
| -1637.57 | 1323.75 |

11. Polygonal Load

Load Type: Flexible
Area of Load: 417396 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -485.349 | -142.076 | 10.2 |
| -1153.62 | -131.529 | 10.2 |
| -1649.21 | 915.592 | 10.2 |
| -1637.57 | 1323.75 | 10.2 |
| -1806.56 | 1468.98 | 5 |
| -1809.13 | 885.67 | 5 |
| -1259.26 | -297.655 | 5 |
| -317.264 | -315.23 | 5 |

12. Polygonal Load

Load Type: Flexible
Area of Load: 941302 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 188.83 | -2491.7 | 10.2 |
| 293.799 | 364.216 | 10.2 |
| 2201.69 | -1376.73 | 10.2 |
| 2690.18 | -1545.21 | 5 |
| 153.042 | 647.667 | 5 |
| 27.7015 | -2645.99 | 5 |

13. Polygonal Load

Load Type: Flexible
Area of Load: 551990 ft²
Depth: 0 ft
Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 952.602 | -2672.52 | 5 |
| 989.748 | -1516.48 | 5 |
| 2690.18 | -1545.21 | 5 |
| 2201.69 | -1376.73 | 10.2 |
| 832.524 | -1353.16 | 10.2 |
| 802.744 | -2507.54 | 10.2 |
| 188.83 | -2491.7 | 10.2 |
| 27.7015 | -2645.99 | 5 |

14. Polygonal Load

Load Type: Flexible

Area of Load: 2.38333e+006 ft²

Depth: 0 ft

Installation Stage: Stage 1

Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|---------|----------|----------------------|
| 832.524 | -1353.16 | 10.2 |
| 2201.69 | -1376.73 | 10.2 |
| 293.799 | 364.216 | 10.2 |
| 188.83 | -2491.7 | 10.2 |
| 802.744 | -2507.54 | 10.2 |

15. Polygonal Load

Load Type: Flexible

Area of Load: 6083.7 ft²

Load: 2.2 ksf

Depth: 0 ft

Installation Stage: Stage 1

Coordinates

| X [ft] | Y [ft] |
|----------|----------|
| -209.08 | -363.999 |
| -12.1921 | -363.999 |
| -11.0259 | -333.141 |
| -208.441 | -333.141 |

16. Polygonal Load

Load Type: Flexible

Area of Load: 34847 ft²

Depth: 0 ft

Installation Stage: Stage 1


Coordinates and Load

| X [ft] | Y [ft] | Load Magnitude [ksf] |
|----------|----------|----------------------|
| -270.312 | -363.597 | 0 |
| -210.328 | -424.303 | 0 |

| | | |
|----------|----------|-----|
| -209.08 | -363.999 | 2.2 |
| -208.441 | -333.141 | 2.2 |
| -11.0259 | -333.141 | 2.2 |
| -12.1921 | -363.999 | 2.2 |
| -209.08 | -363.999 | 2.2 |
| -210.328 | -424.303 | 0 |
| -14.4711 | -424.303 | 0 |
| 64.675 | -363.999 | 0 |
| 64.675 | -333.141 | 0 |
| -8.95688 | -278.393 | 0 |
| -207.308 | -278.393 | 0 |
| -270.312 | -333.141 | 0 |

Soil Layers

| Layer # | Type | Thickness [ft] | Depth [ft] |
|---------|---------------|----------------|------------|
| 1 | CLAY | 7 | 0 |
| 2 | SILT | 7 | 7 |
| 3 | SILT & SAND | 8 | 14 |
| 4 | SAND | 23 | 22 |
| 5 | SAND & GRAVEL | 60 | 45 |



Soil Properties

| Property | CLAY | SILT | SILT & SAND | SAND | SAND & GRAVEL |
|---|------------|----------|-------------|----------|---------------|
| Color | | | | | |
| Unit Weight [kips/ft ³] | 0.118 | 0.117 | 0.12 | 0.122 | 0.124 |
| Saturated Unit Weight [kips/ft ³] | 0.118 | 0.117 | 0.12 | 0.122 | 0.124 |
| Immediate Settlement | Disabled | Enabled | Enabled | Enabled | Enabled |
| Es [ksf] | | 150 | 700 | 900 | 1400 |
| Es bottom [ksf] | | 400 | | | |
| E _{sur} [ksf] | | 150 | 700 | 900 | 1400 |
| E _{sur} bottom [ksf] | | 400 | | | |
| Primary Consolidation | Enabled | Disabled | Disabled | Disabled | Disabled |
| Material Type | Non-Linear | | | | |

| | | | | | | |
|-------------------------|----------|----------|----------|----------|----------|--|
| Cc | 0.32 | | | | | |
| Cr | 0.04 | | | | | |
| e0 | 0.862 | | | | | |
| Pc [ksf] | 4.76 | | | | | |
| OCR | | 1 | 1 | 1 | 1 | |
| Secondary Consolidation | Standard | Disabled | Disabled | Disabled | Disabled | |
| Cae/Ca | 0.004 | | | | | |
| Car/Care | 0.004 | | | | | |

Query Lines

| Line # | Start Location | End Location | Horizontal Divisions | Vertical Divisions |
|--------|--------------------|--------------------|----------------------|--------------------|
| 1 | -37, 1887 | -188, -1959 | 100 | 101 |
| 2 | -114.933, -268.397 | -121.003, -437.214 | 100 | Auto: 61 |

Appendix G

DESIGN OF FABRIC-FORMED CONCRETE MAT (FCM)
Revised August 2013



REVISED JULY 2013

DESIGN OF FABRIC-FORMED CONCRETE MAT (FCM)

FCM IS FOR EROSION PROTECTION OF PERMANENT EXTERIOR SLOPE OF BERMS. FROM FLOODPLAIN ANALYSIS BY CDG, HIGHEST VELOCITIES OCCUR ALONG WEST BERM AT STA. 57.38 (RM),

MAX. VELOCITY = 1.30 TO 1.40 FPS

DEPTH OF FLOW (Y) = EL 481.6 - 465 = 16.6 FT FOR 100-YR FLOOD

FROM FHWA HEC-23, VOL. 2 (SEPT. 2009), CHAPTER 9

$$\text{FACTOR SAFETY (FS)} = \frac{[\mu(t)(\gamma_c - \gamma_w) \cos \theta \cos \alpha - \tau_{DES}]}{\sqrt{[t(\gamma_c - \gamma_w) \sin \theta]^2 + \tau_{DES}^2}}$$

WHERE μ = COEFF. BASE SHEAR = $\tan \delta$
RECOMMENDED δ FOR FCM ON FILTER GEOFABRIC
OVER COHESIVE SOIL IS 32.5°
 $\therefore \mu = \tan(32.5^\circ) = 0.637$

t = THICKNESS OF FCM, TRY HYDROTEx FILTER POINT (FP)
LINER FP220, WHICH IS 2.2" THICK, OR 0.183 FT

γ_c = UNIT WEIGHT OF FINE AGGREGATE CONCRETE

RECOMMENDED $\gamma_c = 130$ PCF

$\gamma_w = 62.4$ PCF (WATER)

θ = SLOPE ANGLE = 18.435° FOR 1(V)-3(H)

α = SLOPE OF BED, ASSUME 0

$$\text{ASSUME F.S.} = 1.5 = \frac{[(0.637)(0.183)(130 \text{ PCF} - 62.4 \text{ PCF}) \cos(18.435^\circ) \cos(0^\circ) - \tau_{DES}]}{\sqrt{[(0.183)(130 - 62.4) \sin 18.435^\circ]^2 + \tau_{DES}^2}}$$

SOLVING, $\tau_{DES} = 1.294$ PSF FOR F.S. = 1.5

$$\text{DESIGN VELOCITY: } \tau_{DES} = \frac{\gamma_w}{Y^{1/3}} \left(\frac{n V_{DES}}{K_u} \right)^2 \quad \text{WHERE } K_u = 1.486 \text{ (ENG. UNITS)}$$


n = MANNING COEFF.
FOR FCM

$$1.294 \text{ PSF} = \frac{62.4 \text{ PCF}}{(16.6')^{1/3}} \left(\frac{0.03 \cdot V_{DES}}{1.486} \right)^2$$

$n = 0.03$ TO 0.025

MAX $V_{DES} = 11.4$ FPS $\gg 1.40$ FPS ESTIMATED

USE: HYDROTEx FP220 OVER GEOFABRIC
OVER COHESIVE BERM FILL



HYDROTEX™

Specification Guideline

Fabric-formed Concrete Erosion Control Systems

Filter Point Lining

Table 1.0 Typical Dimensions and Weights

| Filter Point | FP220 | FP400 | FP600 | FP800 | FP1000 | FP1200 |
|---|-------|-------|-------|-------|--------|--------|
| Average Thickness, mm | 56 | 102 | 152 | 203 | 254 | 305 |
| Mass Per Unit Area, kg/m ² | 121 | 220 | 330 | 440 | 550 | 661 |
| Filter Point Spacing, mm | 127 | 203 | 254 | 305 | 356 | 406 |
| Area per Filter Point, cm ² | 12.9 | 12.9 | 40.7 | 40.7 | 78.7 | 78.7 |
| Perimeter per Filter Point, mm | 165 | 165 | 279 | 279 | 381 | 381 |
| Concrete Coverage, m ² /m ³ | 16.6 | 9.1 | 6.1 | 4.6 | 3.6 | 3.0 |
| Shear Resistance, kg/m ² | 54 | 98 | 146 | 195 | 244 | 293 |

Note: Values shown are typical and will vary with weight of concrete and field conditions.

Product Description

Filter Point Linings with filtering points (drains) provide an erosion resistant, permeable concrete lining for ditches, channels, canals, streams, rivers, ponds, lakes, reservoirs, marinas, and protected port and harbor areas. Filter Point Linings have a cobbled surface and a relatively high coefficient of hydraulic friction in order to achieve lower flow velocities and to reduce wave run-up. The filter points provide for the relief of hydrostatic uplift pressure, increasing the system's stability.

Filter Point Linings are generally used in lieu of stone rip rap or slope paving due to their lower cost and higher performance. Filter Point Linings have greater stability than conventional slope paving because of several factors – they can mitigate uplift pressure from ground water, reduce hydraulic uplift of flowing water by slowing channel velocities, and conform to soil contours during installation to reduce the potential for underscour.

Filter Point forms are woven from multifilament and textured yarns. The double-layer fabric is joined by interwoven filter points on controlled centers to form a lining with a deeply cobbled appearance. The spacing of the filter points determines the lining's thickness and weight, while the specially designed filter points relieve hydrostatic pressure and reduce applied stress to the fabric during pumping. Filter Point Linings are available in a wide range of thicknesses.

1.0 GENERAL

1.1 Scope of Work: The Contractor shall furnish all labor, materials, equipment, and incidentals required to perform all operations in connection with the installation of the proposed Filter Point (FP) Lining in accordance with the lines, grades, design, and dimensions shown on the Contract Drawings and as specified herein.

1.2 Description: The work shall consist of installing an unreinforced concrete lining by positioning specially woven, double-layer synthetic forms on the surface to be protected and filling them with a pumpable, fine aggregate concrete (structural grout) in such a way as to form a stable lining of required thickness, weight and configuration.

2.0 MATERIALS REQUIREMENTS

2.1 Fine Aggregate Concrete: Fine aggregate concrete shall consist of a proportioned mixture of Portland cement, fine aggregate (sand) and water. The consistency of the fine aggregate concrete delivered to the concrete pump shall be proportioned and mixed as to have an efflux time of 9-12 seconds when passed through the 19 mm orifice of the standard flow cone that is described in ASTM C 939. Pozzolan, fluidifier or pumping aid conforming to this Specification may be used at the option of the Contractor. The mix shall exhibit a compressive strength of 13.8 MPa at 28 days, when made and tested in accordance with ASTM C 31 and C 39.

2.1.1 Portland cement shall conform to ASTM C 150, Type I or Type II.

2.1.2 Fine aggregate shall conform to ASTM C 33, except as to grading. Aggregate grading shall be reasonably consistent and shall not exceed the maximum size which can be conveniently handled with available pumping equipment.

PROPERTY REQUIREMENTS - FILTER POINT FABRIC^{1, 2}

| Property | Test Method | Units | Values |
|---|-------------|----------------------|--------------------|
| Physical: | | | |
| Composition of Yarns | | | Nylon or polyester |
| Mass Per Unit Area (double-layer) | ASTM D 5261 | g/m ² | 403 |
| Thickness | ASTM D 5199 | mm | 0.6 |
| Mill Width | | m | 1.92 |
| Mechanical: | | | |
| Wide-Width Strip Tensile Strength - Machine | ASTM D 4595 | kN/m | 24.5 |
| - Cross | | kN/m | 19.3 |
| Elongation at Break - Machine | ASTM D 4595 | % | 20 |
| - Cross | | % | 30 |
| Trapezoidal Tear Strength - Machine | ASTM D 4533 | N | 665 |
| - Cross | | N | 445 |
| Hydraulic: | | | |
| Apparent Opening Size (AOS) | ASTM D 4751 | mm | 0.425 |
| Flow Rate | ASTM D 4491 | l/min/m ² | 3665 |
| Flow Rate through Filter Point | ASTM D 4491 | l/min/m ² | 285 |

Notes:

1. Conformance of fabric to specification property requirements shall be based on ASTM D 4759, "Practice for Determining the Specification Conformance of Geotextiles."
2. All numerical values represent minimum average roll values (i.e., average of test results from any sample roll in a lot shall meet or exceed the minimum values). Lots shall be sampled according to ASTM D 4354, "Practice for Sampling of Geosynthetics for Testing."

2.1.3 Water for mixing shall be clean and free from injurious amounts of oil, acid, salt, alkali, organic matter or other deleterious substances.

2.1.4 Pozzolan, if used, shall conform to ASTM C 618, Class C, F or N.

2.1.5 Plasticizing and air entraining admixtures, if used, shall conform to ASTM C 494 and ASTM C 260, respectively.

2.2 Fabric Forms: The fabric forms shall be as specified, HYDROTEX™ Filter Point (see Note A) forms as manufactured by Geostar Corporation; 74 Perimeter Center East, Suite 7420; Atlanta, Georgia 30346-1803, Tel: 800.253.0561 (770.399.5051); or approved equal. The fabric forms shall be composed of synthetic yarns formed into a woven fabric. Yarns used in the manufacture of the fabric shall be composed of nylon and/or polyester. Forms shall be woven with a minimum of 50% textured yarns (by weight) to improve adhesion to fine aggregate concrete and to improve filtration. Partially-oriented (POY), draw-textured, and/or staple yarns shall not be used in the manufacture of the fabric. Each layer of fabric shall conform to the physical, mechanical and hydraulic requirements referenced herein. The fabric forms shall be free of defects or flaws which significantly affect their physical, mechanical, or hydraulic properties.

Note A: The engineer shall indicate the Filter Point Lining size required (see Table 1.0). Example: FP400.

2.2.1 Fabric forms shall consist of double-layer woven fabric joined together by spaced, interwoven filter points to form a concrete lining with a finished average thick-

ness of (see Table 1.0) mm, a nominal mass per unit area of (see Table 1.0) kg/m², and a deeply cobbled surface appearance. After the form has been filled with fine aggregate concrete, the filter points shall be on approximately (see Table 1.0) mm spacing when measured along the diagonal. Filter points shall be formed by interweaving the double-layer fabric to form water permeable drains and attachment points for the control of concrete lining thickness. The interweaving of the fabric layers shall form an area of double density, high strength, single-layer fabric with an area of (see Table 1.0) cm² and a perimeter of (see Table 1.0) mm. All filter points shall be cross shaped and shall have twill weave centers designed to function as drains to relieve hydrostatic uplift pressure.

2.2.2 Mill widths of fabric shall be a minimum of 1.92 meters. Each selvage edge of the top and bottom layers of fabric shall be reinforced for a width of not less than 35 mm by adding a minimum of 6 warp yarns to each selvage construction. Mill width rolls shall be cut to the length required, and the double-layer fabric separately joined, bottom layer to bottom layer and top layer to top layer, by means of sewing thread, to form multiple mill width panels with sewn seams on not less than 182 cm centers.

2.2.3 All factory-sewn seams shall be downward facing as shown on the Contract Drawings. All seams sewn in the factory shall be not less than 15.7 kN/m when tested in accordance with ASTM D 4884. All sewn seams and zipper attachments shall be made using a double line of U.S. Federal Standard Type 401 stitch. All stitches

shall be sewn simultaneously and be parallel to each other, spaced between 6 and 19 mm apart. Each row of stitching shall consist of 4 to 7 stitches per 25.4 mm. Thread used for seaming shall be nylon and/or polyester.

2.2.4 Baffles shall be installed at predetermined mill width intervals to regulate the distance of lateral flow of fine aggregate concrete. The baffle material shall be non-woven filter fabric. The grab tensile strength of the filter fabric shall be not less than 400 N when tested in accordance with ASTM D 4632.

2.2.5 The fabric forms shall be kept dry and wrapped such that they are protected from the elements during shipping and storage. If stored outdoors, they shall be elevated and protected with a waterproof cover that is opaque to ultraviolet light. The fabric forms shall be labeled as per ASTM D 4873, "Guide for Identification, Storage and Handling of Geosynthetic Rolls."

2.2.6 The Contractor shall submit a manufacturer's certificate that the supplied fabric forms meet the criteria of these Specifications, as measured in full accordance with the test methods and standards referenced herein. The certificates shall include the following information about each fabric form delivered:

Manufacturer's name and current address;
full product name;
style and product code number;
form number(s);
composition of yarns; and
manufacturer's certification statement.

2.3 Filter Fabrics: The filter fabrics shall be composed of synthetic fibers or yarns formed into a nonwoven or woven fabric. Fibers and yarns used in the manufacture of filter fabrics shall be composed of at least 85% by weight of polypropylene, polyester or polyethylene. They shall be formed into a network such that the filaments or yarns retain dimensional stability relative to each other, including selvages. These materials shall conform to the physical requirements shown below. The filter fabric shall be free of defects or flaws which significantly affect its mechanical or hydraulic properties.

PROPERTY REQUIREMENTS - FILTER FABRIC 1, 2

| Property | Test Method | Units | Values |
|---------------------------|-------------|-------------------|--------|
| Grab Tensile Strength | ASTM D 4632 | N | 400 |
| Elongation at Break | ASTM D 4632 | % | 15 |
| Trapezoidal Tear Strength | ASTM D 4533 | N | 130 |
| Permittivity | ASTM D 4491 | sec ⁻¹ | 0.5 |

Notes:

1. Conformance of filter fabrics to specification property requirements shall be based on ASTM D 4759, "Practice for Determining the Specification Conformance of Geotextiles."
2. All numerical values represent minimum average roll values (i.e., average of test results from any sample roll in a lot shall meet or exceed the minimum values). Lots shall be sampled according to ASTM D 4354, "Practice for Sampling of Geosynthetics for Testing."

3.0 DESIGN REQUIREMENTS

Note B: Select the appropriate pair of paragraphs for the final specification based upon the type of hydraulic application.

The average thickness, mass per unit area and hydraulic resistance of each concrete lining shall withstand the hydraulic loadings (velocity, depth, duration, shear stress, pressure, and frequency of immersion) for the design discharges along the structure(s). The stability analysis for each concrete lining shall be accomplished using a factor-of-safety methodology. A minimum factor of safety of 1.5 shall be required.

The Contractor shall provide to the Engineer calculations and design details, provided by the manufacturer or a professional engineer, attesting to the suitability of each fabric formed concrete lining for the purpose contemplated. Each concrete lining shall be accepted only when accompanied by the documented hydraulic performance characteristics derived from tests performed under controlled flow conditions. Test conditions shall conform to test protocol as documented in "Hydraulic Stability of Fabric Formed Concrete Lining and Mat Systems During Overtopping Flow."

or

The average thickness, mass per unit area and hydraulic resistance of each concrete lining shall withstand the hydraulic loadings (depth, duration, type of wave, wave height and period, and pressure distribution) for the design wave. The stability analysis for the concrete lining shall be accomplished using the factor-of-safety methodology. A minimum factor of safety of 1.5 shall be required.

The Contractor shall provide to the Engineer calculations and design details, provided by the manufacturer or a professional engineer, attesting to the suitability of each fabric formed concrete lining for the purpose contemplated. Each concrete lining shall be accepted only when accompanied by hydraulic stability calculations derived from mathematical models developed specifically for fabric formed concrete linings and for this purpose.

4.0 CONSTRUCTION AND INSTALLATION REQUIREMENTS

4.1 Site Preparation

4.1.1 Areas on which fabric forms are to be placed shall be constructed to the lines, grades, contours, and dimensions shown on the Contract Drawings. All obstructions such as roots and projecting stones shall be removed. Where such areas are below the allowable grades, they shall be brought to grade by placing compacted layers of select material. The thickness of layers and the amount of compaction shall be as specified by the Engineer. Where required by the Contract Specifications, soft and otherwise unsuitable subgrade soils shall be identified, excavated and replaced with select materials in accordance with the Contract Specifications.

4.1.2 Excavation and preparation of aprons as well as anchor, terminal or toe trenches shall be done in accordance with the lines, grades, contours, and dimensions shown on the Contract Drawings.

- 4.1.3 Immediately prior to placing the fabric forms, the prepared area shall be inspected by the Engineer, and no forms shall be placed thereon until the area has been approved.

4.2 Fabric Form Placement

- 4.2.1 A filter fabric shall be placed on the graded surface approved by the Engineer.
- 4.2.2 Fabric forms shall be placed over the filter fabric and within the limits shown on the Contract Drawings. Anchoring of the fabric forms shall be accomplished through the use of anchor, terminal and toe trenches.
- 4.2.3 Adjacent fabric forms shall be joined before filling with fine aggregate concrete by field sewing or zippering the two bottom layers of fabric together and the two top layers of fabric together. All field seams shall be made using two lines of U.S. Federal Standard Type 101 stitches. All sewn seams shall be downward facing, and all zipper seams shall be fastened as shown on the Contract Drawings, except with the approval of the Engineer.
- 4.2.4 When conventional joining of fabric forms is impractical or where called for on the Contract Drawings, adjacent forms may be overlapped a minimum of one meter to form a lap joint, pending approval by the Engineer. Based on the predominant flow direction, the downstream edge of the form shall overlap the upstream edge of the next form. In no case shall simple butt joints between forms be permitted.
- 4.2.5 Expansion joints shall be provided as shown on the Contract Drawings, or as specified by the Engineer.
- 4.2.6 Immediately prior to filling with fine aggregate concrete, the assembled fabric forms shall be inspected by the Engineer, and no fine aggregate concrete shall be pumped therein until the fabric seams have been approved. At no time shall the unfilled fabric forms be exposed to ultraviolet light (including direct sunlight) for a period exceeding five days.

4.3 Fine Aggregate Concrete Placement

- 4.3.1 Following the placement of the fabric forms, small slits shall be cut in the top layer of the fabric form to allow the insertion of the filling pipe at the end of the fine aggregate concrete pump hose. These slits shall be of the minimum length to allow proper insertion of the filling pipe. Fine aggregate concrete shall be pumped between the top and bottom layers of fabric, filling the forms to the recommended thickness and configuration.
- 4.3.2 Fine aggregate concrete shall be pumped in such a way that excessive pressure on the fabric forms and cold joints are avoided. A cold joint is defined as one in which the pumping of the fine aggregate concrete into a given form is discontinued or interrupted for an interval of forty-five or more minutes.
- 4.3.3 Holes in the fabric forms left by the removal of the filling pipe shall be temporarily closed by inserting a piece of nonwoven fabric or similar material. The nonwoven fabric shall be removed when the concrete is no longer fluid and the concrete surface at the hole shall be cleaned and smoothed by hand. Foot traffic on the filled form shall be restricted to an absolute minimum for one hour after filling.
- 4.3.4 After the fine aggregate concrete has set, all anchor, terminal and toe trenches shall be backfilled and compacted, as specified by the Engineer.
- 4.3.5 The Filter Point Lining shall be measured by the number of square meters computed from the payment lines shown on the Contract Drawings or from payment lines established in writing by the Engineer. This includes Filter Point fabric forms, fine aggregate concrete, and filter fabric used in the aprons, overlaps, and anchor, terminal, or toe trenches. Slope preparation, excavation and backfilling, and bedding are separate pay items.

Spec: FP (siu)
Revised December 2001

Call or write for your complete set of HYDROTEX™ and HYDROCAST™ Specification Guidelines. Available as printed specifications, in Adobe® Acrobat® (pdf) format, or in an editable text format. PDF specifications are available for download from our web site at www.geostarcorporation.com.

Hydrotex products are manufactured by:

Geostar Corporation
74 Perimeter Center East, Suite 7420
Atlanta, Georgia 30346-1803
Tel: 1.800.253.0561 or 770.399.5051 Fax: 770.394.5999
www.geostarcorporation.com • e-mail: info@geostarcorporation.com

Hydrotex and Hydrocast are trademarks of Geostar Corporation.
2001 Geostar Corporation • Printed in U.S.A.

The information contained herein is furnished without charge or obligation, and the recipient assumes all responsibility for its use. Because conditions of use and handling may vary and are beyond our control, we make no representation about, and are not responsible for, the accuracy or reliability of said information or the performance of any product. Any specifications, properties or applications listed are provided as information only and in no way modify, enlarge or create any warranty. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.

Appendix K

Soil Material Volume and
Balance Calculations
Revised August 2013

**Ameren Missouri Labadie Energy Center
Construction Permit Application for a
Proposed Utility Waste Landfill
Franklin County, Missouri**

December 2012, Revised August 2013

**Appendix K
Soil Material Volume and Balance Calculations**

Appendix K contains calculations of soil needed (required) for construction of the Ameren Missouri Labadie Energy Center Utility Waste Landfill (UWL), and the soil available on-site for the construction. Soil is required for construction of the four general components of the UWL: perimeter berms; liner system; intermediate cover; and final cover system. Operational cover (intermediate) is proposed based on the characteristics of the coal combustion products (CCPs) that will be placed in the UWL.

The perimeter berms are designed with 3:1 side slopes, with a typical berm height of 23 feet, and a 12-foot wide access road on top of the berm. The exterior perimeter berm slopes will be lined with a 2.2-in thick, fabric-formed articulated concrete mat. A 2-feet thick compacted clay liner will be placed on the inside slope of the berm to tie-in with the landfill liner in each phase.

The UWL's final cover system will be two (2) feet of nominally compacted soil capable of sustaining vegetation, underlain by a geotextile cushion, which is underlain by a geomembrane liner.

Three general soil types will be used for construction of the UWL components: Liner-quality, non liner-quality, and vegetative soil. Liner-quality soil describes clayey soils that would meet the requirements of 10 CSR 11.010(10)(B)1 for the landfill liner. Non liner-quality soil describes low plastic clayey soil, silty soils, or sandy soils present at the site. Non liner-quality soils would not be suitable for the landfill liner, but would be used for the construction of the core of the perimeter berms. Vegetative soil describes soils that are capable of sustaining vegetation for the UWL final cover or the outside slopes of the perimeter berms.

The following table summarizes the pertinent acreages and berm volumes for each utility waste landfill component. The acreages and berm volumes were determined from the AutoCAD drawings that depict the three storm water ponds and the layout of the four disposal phases.

| UWL Component | Design Parameters | Notes/Comments |
|----------------------|--------------------------|------------------------------|
| Phase 1 | Cell 1: 31.4 acres | Stormwater Pond 1: 5.7 acres |
| Phase 2 | Cell 2: 35.2 acres | |

| | | |
|--------------------------------------|--------------------|---|
| Phase 3 | Cell 3: 57.1 acres | Stormwater Pond 2: 4.4 acres |
| Phase 4 | Cell 4: 42.8 acres | Stormwater Pond 3: 3.4 acres |
| Total Permitted Disposal Area | 166.5 acres | Includes Cells 1 through 4, excludes the Stormwater Ponds. |
| Stormwater Pond 1 | 5.7 acres | Area at 488' contour |
| Stormwater Pond 2 | 4.4 acres | Area at 488' contour |
| Stormwater Pond 3 | 3.4 acres | Area at 488' contour |
| Total Area for Excavation | 180.0 acres | Includes Phases 1 through 4 and the Stormwater Ponds. |

| | | |
|-------------------------------------|--------------------|--|
| Final "Top of Landfill" Area | 73.7 acres | Final "flat" top of UWL at closure. |
| Final "Exterior Side Slopes" Area | 92.8 acres | Final slopes at closure. |
| Total Final Area for Closure | 166.5 acres | Total Acreage Requiring Final Cap |

All calculated volumes of soil, both needed and available, are rounded up to the nearest 1,000 yd³.

The total soil balance for Phases 1 through 4 and the three stormwater ponds, for clay liner, final cap (top and side slopes), and all perimeter berms, reveals a total soil shortage of 2,750,000 CY of on-site soils within the foot print of Phases 1 through 4 and the three stormwater ponds.

Soils available: 1,260,000 CY

Soils needed: (perimeter berms, liner, intermediate and final cover): 4,010,000 CY

Net soil balance for the landfill: -2,750,000CY

An estimated 2,600,000 CY of liner-quality soil is available from a borrow area in Callaway County on property owned by Ameren Missouri. This is greater than the 639,000 CY of liner-quality soil needed. A contractor will supply additional soil for berm core fill and vegetative cover.

**Ameren Missouri Labadie Energy Center
Proposed Utility Waste Landfill
Franklin County, Missouri**

December 2012, REVISED August 2013

**Appendix K
Soil Material Volume and Balance Calculations**

Note: All calculated volumes are rounded to the nearest 1,000 CY.
Stripping depth of 1.63 ft is the required minimum for volume of final cover.
Soil balance calculations utilized the minimum stripping depth required.
Stripping depth of 1.75 ft is recommended.

Lifetime Construction: Phases 1 through 4 and Stormwater Ponds

ESTIMATE OF TOTAL SOIL NEEDED

ESTIMATE OF NOMINALLY COMPACTED FINAL COVER SOIL NEEDED

SOIL TYPE REQUIRED: Vegetative

Volume (CY) = Area (AC) x 43,560 SF/AC x 2 ft x 1.1 [shrinkage factor] / 27 CF/CY

Total Area 166.5 AC

Total Volume of 2 ft Nominally Compacted Final Cover 166.5 AC= **591,000 CY**

ESTIMATE OF UWL LINER SOIL REQUIRED

SOIL TYPE REQUIRED: Liner Quality

Volume (CY) = Area (AC) x 43,560 SF/AC x 2 ft x 1.1 [shrinkage factor] / 27 CF/CY

Disposal Areas 166.5 AC= **591,000 CY**

Pond Areas 13.5 AC= **48,000 CY**

Total Area 180.0 AC

Total Volume of 2 ft Liner for Disposal Area and Ponds 180.0 AC= **639,000 CY**

ESTIMATE OF GENERAL FILL NEEDED UNDER UWL

SOIL TYPE REQUIRED: Non-Liner Quality

From CADD cut/fill volumes - design grade to existing grade.

Volume of General Site Fill Under UWL & Pond Floors **780,000 CY**

ESTIMATE OF PERIMETER BERM CORE FILL SOIL NEEDED

SOIL TYPE REQUIRED: Non-Liner Quality

From CADD cut/fill volumes - design grade to existing grade, less 2-ft clay liner on slope.

Phase 1 204,115 CY

Phase 2 165,531 CY

Phase 3 393,858 CY

Phase 4 293,945 CY

Pond 1 99,269 CY

Pond 2 93,713 CY

Pond 3 65,730 CY

Total Perimeter Berm Volumes **1,316,162 CY**

ESTIMATE OF GENERAL FILL NEEDED TO REPLACE 1.63' STRIPPING UNDER UWL

SOIL TYPE REQUIRED: Non-Liner Quality

Volume (CY) = Area (225 AC) x Depth (1.63 ft) x 43,560 SF/AC / 27 CF/CY

Volume of Fill to Replace 1.63-ft Stripping in Construction Footprint **592,000 CY**

**Ameren Missouri Labadie Energy Center
Proposed Utility Waste Landfill
Franklin County, Missouri**

December 2012, REVISED August 2013

**Appendix K
Soil Material Volume and Balance Calculations**

ESTIMATE OF INTERMEDIATE COVER (IC) NEEDED

SOIL TYPE REQUIRED: Non-Liner

Assumes reuse of IC and maximum area requiring IC < 57 AC

Volume (CY) = Area (57 AC) x Depth (1 ft) x 43,560 SF/AC / 27 CF/CY

| | |
|------------------------------|------------------|
| Volume of Intermediate Cover | 92,000 CY |
|------------------------------|------------------|

ESTIMATE OF TOTAL SOIL NEEDED

Intermediate Cover

| | |
|--|------------------|
| Volume of Intermediate Cover Soil Needed | 92,000 CY |
|--|------------------|

Liner and Cover Systems

| | |
|-----------------------------------|------------|
| Volume of Final Cover Soil Needed | 591,000 CY |
|-----------------------------------|------------|

| | |
|-----------------------------|------------|
| Volume of Liner Soil Needed | 639,000 CY |
|-----------------------------|------------|

| | |
|--|---------------------|
| Total Needed for Liner and Final Cover Systems | 1,230,000 CY |
|--|---------------------|

General Fill and Perimeter Berm Soil Needs

| | |
|---|------------|
| Volume of General Site Fill Under UWL & Pond Floors | 780,000 CY |
|---|------------|

| | |
|--|--------------|
| Volume of Perimeter Berm Core Fill Soil Needed | 1,316,000 CY |
|--|--------------|

| | |
|--|------------|
| Volume of 1.63-ft. Stripping Replacement | 592,000 CY |
|--|------------|

| | |
|--|---------------------|
| Total Needed for General Fill and Perimeter Berm | 2,688,000 CY |
|--|---------------------|

| | |
|--|---------------------|
| Estimated Total Volume of Soil Needed | 4,010,000 CY |
|--|---------------------|

ESTIMATE OF SOIL-SPECIFIC REQUIREMENTS

| | |
|-------------------------------------|------------|
| Volume of Liner Quality Soil Needed | 639,000 CY |
|-------------------------------------|------------|

| | |
|--|------------|
| Volume of Vegetative Quality Soil Needed | 683,000 CY |
|--|------------|

| | |
|---|--------------|
| Volume of Non-Liner Quality Soil Needed | 2,688,000 CY |
|---|--------------|

| | |
|--|---------------------|
| Estimated Total Volume of Soil Needed | 4,010,000 CY |
|--|---------------------|

ESTIMATE OF TOTAL SOIL AVAILABLE

Assumes 1.63 ft of vegetative soil will be excavated from the 225 AC area, 5% swell.

| | |
|--|------|
| Liner Quality Soil to be Excavated from the Construction Footprint | 0 CY |
|--|------|

| | |
|---|------------|
| Vegetative Soil to be Excavated from the Construction Footprint | 621,000 CY |
|---|------------|

| | |
|--|------|
| Non-Liner Quality Soil to be Excavated from the Construction Footprint | 0 CY |
|--|------|

| | |
|--|-------------------|
| Total Soil to be Excavated from the Construction Footprint | 621,000 CY |
|--|-------------------|

| | |
|---|------------|
| Liner Quality Soil to be Excavated from the Borrow Area | 639,000 CY |
|---|------------|

Made to equal liner soil needed. No surplus from borrow included

| | |
|--|------|
| Vegetative Soil to be Excavated from the Borrow Area | 0 CY |
|--|------|

| | |
|---|------|
| Non-Liner Quality Soil to be Excavated from the Borrow Area | 0 CY |
|---|------|

| | |
|---|-------------------|
| Total Soil to be Excavated from the Borrow Area | 639,000 CY |
|---|-------------------|

| | |
|--|------------|
| Volume of Liner Quality Soil Available | 639,000 CY |
|--|------------|

| | |
|-------------------------------------|------------|
| Volume of Vegetative Soil Available | 621,000 CY |
|-------------------------------------|------------|

| | |
|--|------|
| Volume of Non-Liner Quality Soil Available | 0 CY |
|--|------|

| | |
|-----------------------------|---------------------|
| Total Soil Available | 1,260,000 CY |
|-----------------------------|---------------------|

**Ameren Missouri Labadie Energy Center
Proposed Utility Waste Landfill
Franklin County, Missouri**

December 2012, REVISED August 2013

**Appendix K
Soil Material Volume and Balance Calculations**

SOIL BALANCE FOR PHASES 1 THROUGH 4 AND THE STORMWATER PONDS

TOTAL SOIL BALANCE

| | |
|------------------------------------|----------------------|
| Estimated Volume of Soil Needed | 4,010,000 CY |
| Estimated Volume of Soil Available | <u>1,260,000 CY</u> |
| Soil Balance | -2,750,000 CY |

SOIL SPECIFIC BALANCE

| | |
|--|-------------------|
| Estimated Volume of Liner Quality Soil Needed | 639,000 CY |
| Estimated Volume of Liner Quality Soil Available | <u>639,000 CY</u> |
| Liner Quality Soil Balance | 0 CY |

| | |
|---|-------------------|
| Estimated Volume of Vegetative Soil Needed | 683,000 CY |
| Estimated Volume of Vegetative Soil Available | <u>621,000 CY</u> |
| Vegetative Quality Soil Balance | -62,000 CY |

| | |
|--|----------------------|
| Estimated Volume of Non-Liner Quality Soil Needed | 2,688,000 CY |
| Estimated Volume of Non-Liner Quality Soil Available | <u>0 CY</u> |
| Non-Liner Quality Soil Balance | -2,688,000 CY |

LANDFILL SYSTEMS BALANCE

| | |
|--|-------------------|
| Estimated Liner Quality Soil for Liner Needed | 639,000 CY |
| Estimated Liner Quality Soil for Liner Available | <u>639,000 CY</u> |
| Liner and Cover System Liner Quality Soil Balance | 0 CY |

| | |
|---|-------------------|
| Estimated Volume of Vegetative Soil for Cover Systems Needed | 683,000 CY |
| Estimated Volume of Vegetative Soil for Cover Systems Available | <u>621,000 CY</u> |
| Cover Sytem Vegetative Soil Balance | -62,000 CY |

GENERAL FILL AND PERIMETER BERM BALANCE

| | |
|---|----------------------|
| Estimated Volume of General Fill and Permieter Berm Core Fill Needed | 2,688,000 CY |
| Estimated Volume of General Fill and Permieter Berm Core Fill Available | <u>0 CY</u> |
| General Fill and Perimeter Berm Core Fill Balance | -2,688,000 CY |

Appendix L

Landfill Life Estimate

**Ameren Missouri Labadie Energy Center
Proposed Utility Waste Landfill
Franklin County, Missouri**

January 2013

**Appendix L
Landfill Life Estimate**

The life of the proposed utility waste landfill (UWL) is estimated based on projected waste volume production rates and the calculated net UWL volume. The total UWL volume was estimated using CADD to measure the volume between a surface 2-feet below the final cover (to adjust for the final cover thickness of 2-feet) and a surface 1-foot above the top-of-liner (to adjust for the protective cover thickness of 1-foot). The net UWL volume was then determined by deducting a volume equal to the area of the relatively flat floor (146.6 acres) times a thickness of 1-foot, to account for the volume occupied by the leachate drainage aggregate layer.

Gross UWL Airspace Volume = 16,513,000 CY

Drainage Layer Volume = 1 ft x 146.6 AC x 43,560 SF/AC x 1 CY/ 27 CF = 236,500 CY

Protective Cover Volume = 1 ft x 166.5 AC x 43,560 SF/AC x 1 CY/ 27 CF = 268,600 CY

Final Cover Volume = 2 ft x 166.5 AC x 43,560 SF/AC x 1 CY/27 CF = 537,200 CY

Net Waste Volume = 16,513,000 – 236,500 - 268,600 - 537,200 = 15,470,700 CY

Two wet flue gas desulfurization (WFGD) systems will come on line at different times, increasing the rate of coal combustion product (CCP) generation over time. The generations rates projected are:

- 2015 to 2019, 2.3 MCY,
- 2020 to 2024, 2.9 MCY,
- 2025 to 2029, 3.6 MCY, and
- 2030 and after, 3.8 MCY every five year period or 760,000 CY/year.*

The amount of landfill volume remaining after the first 15 years would be:

$$15.5 \text{ MCY} - 2.3 \text{ MCY} - 2.9 \text{ MCY} - 3.6 \text{ MCY} = 6.7 \text{ MCY}$$

The years of life available in the remaining volume is:

$$6.7 \text{ MCY} / 760,000 \text{ CY/year} = 8.8 \text{ years}$$

The total landfill life is:

$$15.0 + 8.8 = 23.8 \text{ years}$$

* CCP production estimates are drawn from the Reitz & Jens Design Basis dated October 16, 2012.

Appendix M

Erosion Calculations

**Ameren Missouri Labadie Energy Center
Proposed Utility Waste Landfill
Franklin County, Missouri
December 2012**

**Amendments to Erosion Calculations
Appendix M**

EROSION PROTECTION CALCULATIONS


The stormwater drainage structures were checked for erosion control by utilizing the Erosion Control Materials Design Software 4.3 (ECMDS) by North American Green (NAG). This software analyzes erodibility of various channel/slope configurations. The channel/slope is analyzed for erodibility based upon soil type, cover, flow-rate, velocity, Manning's number and channel grade. Channel sections representative of the side slope benches and letdown ditches have been analyzed for erosion using riprap.

SUMMARY OF DESIGN ANALYSIS

1. Typical Landfill Slope Erosion Protection

The typical top of landfill was modeled for erosion using ECDMS, which uses a version of the Revised Universal Soil Loss Equation (RUSLE). The top of the landfill is designed with a minimum 2 percent slope. The maximum distance along the 2 percent slope is 550 ft. The annual soil loss of 0.013 inches per year is less than the permissible 0.03 inches per year, and is considered acceptable (a standard value in ECDMS; see Table 1 and Figure 1a).

The typical side slope was also modeled for erosion using ECDMS. The 3:1 side slope of 225 ft is broken into two sections of approximately 117 ft and 108 ft by a bench at 520 feet elevation. Both segments have annual soil losses less than 0.03 in. The segment with the larger annual soil loss eroded at a rate of 0.017 in/yr (see Table 1 and Figures 1a and 1b).



2. Typical Diversion Structure on Top of Landfill

Flow from the top of the landfill will be directed to the letdowns using diversion structures. The typical diversion structure would have a slope of up to 1 percent, a depth of 1 ft, and side slope of 50:1 and 3:1. ECMDS was used to calculate shear stress resulting from the maximum flow of 4.5 cfs (half the maximum flow in a letdown). Shear stresses were within permissible levels (see Table 1 and Figure 2).

3. Typical Landfill Letdown Structure

The standard letdown design to be utilized at the Ameren Missouri Labadie Power Plant Utility Waste Landfill (8 ft wide bottom and 3:1 side slopes) was checked for permissible shear stress using two types of cover (reinforced vegetation and 22-in riprap). ECMDS was used to calculate shear stress resulting from the maximum flow of 8.9 cfs on the 3:1 bottom slope of the letdowns. The letdown structure flow was calculated in Appendix N using the Rational method, a 25-year, 1-hour storm, the largest area drained by a letdown structure. Shear stresses were within permissible levels (see Table 1 and Figure 3a and 3b).

4. Typical Bench

Benches on the side slope are proposed. They will be at 520 ft elevation and have 1 percent bottom slopes. The bench side slopes will be 3:1 on one side and 10:1 on the other, with a depth of 1.5 ft. As with the letdown structures, these were modeled using ECMDS. The permissible shear stress for a fair stand of vegetation is greater than the estimated shear stress created by a flow of 4.5 cfs (half the maximum flow in a letdown; see Table 1 and Figure 4).

5. Perimeter Ditch

The standard perimeter ditch to be utilized at the Ameren Missouri Labadie Power Plant Utility Waste Landfill (9 ft wide bottom and 3:1 side slopes) was checked for permissible shear stress using a fair stand of unreinforced vegetation. ECMDS was used to calculate shear stress resulting from the maximum flow of 36 cfs. Shear stresses were within permissible levels (see Table 1 and Figure 5).

TABLES

**Ameren Missouri Labadie Energy Center
Proposed Utility Waste Landfill
Franklin County, Missouri**

**Summary Table of Erosion Control
Table 1**

| | Structure | Description of Cover and Conditions | Safety Factor | Limitations | | |
|----|--|---|---------------|-----------------|-------------|--------------|
| | | | | Limiting Factor | Permissible | Calculated |
| 1a | Typical Top of Landfill | Unreinforced vegetation with a fair stand of bunch growth | 2.232 | Soil Loss | 0.03 in/yr | 0.013 in/yr |
| 1b | Typical Side Slope Below Bench | 117 feet of cover with an excellent stand of sod growth | 2.284 | Soil Loss | 0.03 in/yr | 0.013 in/yr |
| | Typical Side Slope Above Bench | 108 feet of cover with a good stand of mixed bunch and sod growth | 1.816 | Soil Loss | 0.03 in/yr | 0.017 in/yr |
| 2 | Typical Diversion Structure on Top of Landfill | Unreinforced vegetation with a fair stand of bunch growth | 9.04 | Shear Stress | 4.20 psf | 0.46 psf |
| 3a | Typical Letdown | Reinforced vegetation | 1.55 | Shear Stress | 7.00 psf | 4.52 psf |
| 3b | Typical Letdown | RipRap | 1.23 | Shear Stress | 7.33 psf | 5.98 psf |
| 4 | Typical Bench | Unreinforced vegetation with a fair stand of bunch growth | 6.49 | Shear Stress | 4.20 psf | 0.65 psf |
| 5 | Typical Perimeter Ditch | Good stand of mixed bunch and sod growth | 70.17 | Shear stress | 0.035 psf | 0.000499 psf |

FIGURES

Ameren Missouri Labadie Power Plant
Proposed Utility Waste Landfill
Franklin County, Missouri
Appendix M
Typical Top of Landfill
Figure 1a

| | | | | | |
|--|--|---------------------|--|--|--|
| North American Green - ECMD5 Version 4.3 | | 10/31/2012 08:10 AM | | COMPUTED BY: | |
| PROJECT NAME: Ameren Missouri Labadie | | PROJECT NO.: | | SLOPE DESCRIPTION: Typical Top of Landfill | |

| | | |
|----------------------------|---------------|------------------------------|
| Country | United States | <p>Slope Gradient = 50:1</p> |
| State/Region | Missouri | |
| City | St. Louis | |
| Annual R Factor | 210 | |
| Total Slope Length (ft) | 550 | |
| Protection Type | Permanent | |
| Protection Period (months) | | |
| Beginning Month | | |
| Adjusted R Value | 210 | |
| Slope Gradient (H:1) | 50 | |
| Soil Type | Silt Loam | Not to Scale |
| K Factor | 0.33 | |
| Soil Loss Tolerance (in) | 0.03 | |

| Reach | Cum. Begin (ft) | Cum. End (ft) | Material | Vegetation Type Growth Habit | Density | ASL bare (in) | ASL mat (in) | SLT (in) | SF | Remarks |
|-------|-----------------|---------------|-----------|------------------------------|---------|---------------|--------------|----------|-------|---------|
| 1 | 0 | 550 | Estb. Veg | Bunch Type | 50-75% | 0.134 | 0.013 | 0.03 | 2.232 | STABLE |
| 2 | | | | | | | | | | |
| 3 | | | | | | | | | | |
| | 0 | 550 | Composite | | | 0.134 | 0.013 | | | |

Vegetation Density=Percentage of soil coverage provided by vegetation
ASLbare=Average Soil Loss potential of unprotected soil (uniform inches)
MSLbare=Maximum Soil Loss potential on unprotected soil (uniform inches)
SLT=Soil Loss Tolerance for slope segment (uniform inches)
Composite=Average soil loss from total slope length (uniform inches)

C=Cover material performance factor (Fraction of soil loss of unprotected)
ASLmat=Average Soil Loss potential w/material (uniform inches)
MSLmat=Maximum Soil Loss potential w/material (uniform inches)
SF=Safety Factor

Ameren Missouri Labadie Power Plant
Proposed Utility Waste Landfill
Franklin County, Missouri
Appendix M
Typical Side Slope
Figure 1b

North American Green - ECMS Version 4.3 6/14/2012 04:31 PM COMPUTED BY:

PROJECT NAME: Ameren Missouri Labadie PROJECT NO.: SLOPE DESCRIPTION:

Country: United States
State/Region: Missouri
City: St. Louis
Annual R Factor: 210
Total Slope Length (ft): 225
Protection Type: Permanent
Protection Period (months):
Beginning Month:
Adjusted R Value: 210
Slope Gradient (H:1): 3
Soil Type: Silt Loam
K Factor: 0.33
Soil Loss Tolerance (in): 0.03

Slope Gradient = 3:1

| Reach | Cum. Dist. Begin (ft) | Cum. Dist. End (ft) | Material | Vegetation Type Growth Habit | Density | ASL bare (in) | ASL mat (in) | SLT (in) | SF | Remarks |
|-------|-----------------------|---------------------|------------|------------------------------|---------|---------------|--------------|----------|-------|---------|
| 1 | 0 | 108 | Estb. Veg. | Mix (Both Sod/Bunch) | >=95% | 2.360 | 0.017 | 0.03 | 1.816 | STABLE |
| 2 | 108 | 225 | Estb. Veg. | Sod Former | >=95% | 4.378 | 0.013 | 0.03 | 2.284 | STABLE |
| 3 | 0 | 225 | Composite | | | 3.409 | 0.015 | | | |

Vegetation Density=Percentage of soil coverage provided by vegetation
ASLbare=Average Soil Loss potential of unprotected soil (uniform inches)
MSLbare=Maximum Soil Loss potential on unprotected soil (uniform inches)
SLT=Soil Loss Tolerance for slope segment (uniform inches)
Composite=Average soil loss from total slope length (uniform inches)


C=Cover material performance factor (Fraction of soil loss of unprotected)
ASLmat=Average Soil Loss potential w/material (uniform inches)
MSLmat=Maximum Soil Loss potential w/material (uniform inches)
SF=Safety Factor

Ameren Missouri Labadie Power Plant
Proposed Utility Waste Landfill
Franklin County, Missouri
Appendix M
Typical Diversion Structure on Top of Landfill
Figure 2

| | | | |
|--|-------------------|----------------------------------|-------------------|
| North American Green - ECADS Version 4.3 | | 10/31/2012 08:15 AM COMPUTED BY: | |
| PROJECT NAME: Ameren Missouri Labadie | | PROJECT NO.: | |
| FROM STATION/REACH: | TO STATION/REACH: | DRAINAGE AREA: | DESIGN FREQUENCY: |

HYDRAULIC RESULTS

| Discharge (cfs) | Peak Flow Period (hrs) | Velocity (fps) | Area (sq ft) | Hydraulic Radius (ft) | Normal Depth (ft) |
|-----------------|------------------------|----------------|--------------|-----------------------|-------------------|
| 4.5 | 1.0 | 0.31 | 14.68 | 0.37 | 0.74 |



LINER RESULTS

Not to Scale


| Reach | Matting Type | Stability Analysis | Vegetation Characteristics | | | | Permissible Shear Stress (psf) | Calculated Shear Stress (psf) | Safety Factor | Remarks |
|----------|----------------|--------------------|----------------------------|-------|-----------|---------|--------------------------------|-------------------------------|---------------|---------|
| | Staple Pattern | | Phase | Class | Type | Density | | | | |
| Straight | Unreinforced | Vegetation | | C | Mix | 50-75% | 4.20 | 0.46 | 9.04 | STABLE |
| | | Soil | | | Silt Loam | | 0.035 | 0.001 | 48.47 | STABLE |

Ameren Missouri Labadie Power Plant
Proposed Utility Waste Landfill
Franklin County, Missouri
Appendix M
Typical Reinforced Vegetation Letdown Structure
Figure 3a

| | | | | | |
|--|--|-------------------|----------------------------------|-------------------|--|
| North American Green - ECMD5 Version 4.3 | | | 10/31/2012 10:17 AM COMPUTED BY: | | |
| PROJECT NAME: Ameren Missouri Labadie | | | PROJECT NO.: | | |
| FROM STATION/REACH: | | TO STATION/REACH: | | DRAINAGE AREA: | |
| | | | | DESIGN FREQUENCY: | |

HYDRAULIC RESULTS

| Discharge (cfs) | Peak Flow Period (hrs) | Velocity (fps) | Area (sq.ft) | Hydraulic Radius (ft) | Normal Depth (ft) |
|-----------------|------------------------|----------------|--------------|-----------------------|-------------------|
| 8.9 | 1.0 | 4.74 | 1.88 | 0.20 | 0.22 |



LINER RESULTS

Not to Scale


| Reach | Matting Type | Stability Analysis | Vegetation Characteristics | | | | Permissible Shear Stress (psf) | Calculated Shear Stress (psf) | Safety Factor | Remarks |
|----------|----------------|--------------------|----------------------------|-------|-----------|---------|--------------------------------|-------------------------------|---------------|---------|
| | Staple Pattern | | Phase | Class | Type | Density | | | | |
| Straight | SC250 | Vegetation | 2 | D | Mix | 75-95% | 7.00 | 4.52 | 1.55 | STABLE |
| | Staple E | Soil | | | Silt Loam | | 2.500 | 0.470 | 5.32 | STABLE |

Ameren Missouri Labadie Power Plant
Proposed Utility Waste Landfill
Franklin County, Missouri
Appendix M
Typical Riprap Letdown Structure
Figure 3b

| | | | | |
|--|-------------------|---------------------|-------------------|--------------|
| North American Green - ECMD5 Version 4.3 | | 10/31/2012 10:19 AM | | COMPUTED BY: |
| PROJECT NAME: Ameren Missouri Labadie | | PROJECT NO.: | | |
| FROM STATION/REACH: | TO STATION/REACH: | DRAINAGE AREA: | DESIGN FREQUENCY: | |

HYDRAULIC RESULTS

| Discharge (cfs) | Peak Flow Period (hrs) | Velocity (fps) | Area (sq ft) | Hydraulic Radius (ft) | Normal Depth (ft) |
|-----------------|------------------------|----------------|--------------|-----------------------|-------------------|
| 8.9 | 1.0 | 3.49 | 2.55 | 0.26 | 0.29 |



LINER RESULTS

Not to Scale

| Reach | Matting Type | Stability Analysis | Vegetation Characteristics | | | | Permissible Shear Stress (psf) | Calculated Shear Stress (psf) | Safety Factor | Remarks |
|----------|----------------|--------------------|----------------------------|-------|------|---------|--------------------------------|-------------------------------|---------------|---------|
| | Staple Pattern | | Phase | Class | Type | Density | | | | |
| Straight | Rock Riprap | Unvegetated | | | | | 7.33 | 5.98 | 1.23 | STABLE |
| | 22in | | | | | | | | | |


[Back to Input Screen](#)

Ameren Missouri Labadie Power Plant
Proposed Utility Waste Landfill
Franklin County, Missouri
Appendix M
Typical Bench
Figure 4

| | | | | |
|--|--|---------------------|--|-------------------|
| North American Green - ECMD5 Version 4.3 | | 10/31/2012 10:20 AM | | COMPUTED BY: |
| PROJECT NAME: Ameren Missouri Labadie | | PROJECT NO.: | | |
| FROM STATION/REACH: | | DRAINAGE AREA: | | DESIGN FREQUENCY: |

HYDRAULIC RESULTS

| Discharge (cfs) | Peak Flow Period (hrs) | Velocity (fps) | Area (sq ft) | Hydraulic Radius (ft) | Normal Depth (ft) |
|-----------------|------------------------|----------------|--------------|-----------------------|-------------------|
| 4.5 | 1.0 | 0.64 | 7.00 | 0.51 | 1.04 |



LINER RESULTS


Not to Scale

| Reach | Matting Type | Stability Analysis | Vegetation Characteristics | | | | Permissible Shear Stress (psf) | Calculated Shear Stress (psf) | Safety Factor | Remarks |
|----------|----------------|--------------------|----------------------------|-------|-----------|---------|--------------------------------|-------------------------------|---------------|---------|
| | Staple Pattern | | Phase | Class | Type | Density | | | | |
| Straight | Unreinforced | Vegetation | | C | Bunch | 50-75% | 4.20 | 0.65 | 6.49 | STABLE |
| | | Soil | | | Silt Loam | | 0.035 | 0.004 | 8.06 | STABLE |

Ameren Missouri Labadie Power Plant
Proposed Utility Waste Landfill
Franklin County, Missouri
Appendix M
Typical Perimeter Berm
Figure 5

| | | | | | | |
|--|---------------------------|-------------------|--------------|-------------------------|----------------------|-------------------|
| North American Green - ECMDS Version 4.3 | | | | 11/03/2012 08:23 AM | | COMPUTED BY: |
| PROJECT NAME: Ameren Missouri Labadie | | | | PROJECT NO.: | | |
| FROM STATION/REACH: | | TO STATION/REACH: | | DRAINAGE AREA: | | DESIGN FREQUENCY: |
| HYDRAULIC RESULTS | | | | | | |
| Discharge (cfs) | Peak Flow Period (hrs) | Velocity (fps) | Area (sq.ft) | Hydraulic Radius(ft) | Normal Depth (ft) | |
| 36.0 | 1.0 | 0.32 | 112.74 | 2.86 | 4.81 | |

Unreinforced Vegetation (n=0.094)



LINER RESULTS

Not to Scale

| Reach | Matting Type | Stability Analysis | Vegetation Characteristics | | | | Permissible Shear Stress (psf) | Calculated Shear Stress (psf) | Safety Factor | Remarks |
|----------|----------------|--------------------|----------------------------|-----------|-------|---------|--------------------------------------|-------------------------------------|---------------|---------|
| | Staple Pattern | | Phase | Class | Type | Density | | | | |
| Straight | Unreinforced | Vegetation | | C | Bunch | 50-75% | 4.20 | 0.03 | 139.90 | STABLE |
| | | Soil | | Silt Loam | | | 0.035 | 0.000499 | 70.17 | STABLE |

Appendix N

Stormwater Calculations

**Ameren Missouri Labadie Energy Center
Proposed Utility Waste Landfill
December 2012**

Appendix N

STORMWATER DRAINAGE STRUCTURE SUMMARY

10 CSR 80-11.010 (8)(B)1.F.II of the Missouri Solid Waste Management Regulations requires that "On-site drainage structures and channels shall be designed to prevent flow onto the active portion of the utility waste landfill during peak discharge from at least a twenty-five (25)-year storm..." 10 CSR 80-11.010 (8)(B)1.F.III of the Missouri Solid Waste Management Regulations requires that "On-site drainage structures and channels shall be designed to collect and control at least the water volume resulting from a twenty-four (24)-hour, twenty-five (25)-year storm." In this document, the capacities of the stormwater drainage structures are calculated and compared to expected storm flows using the Rational Method equation. Channel design calculations utilized a 1-hour, 25-year storm intensity as the basis for estimating runoff and peak discharge. The 1-hour intensity storm results in a larger peak flow than the 24-hour intensity storm. Pond storage capacity calculations utilized the 24-hour, 25-year storm intensity for the peak design volume.

Drainage Areas and Flows

To determine the spacing of letdown structure, limits on the grade within the side benches were set. The flow line of the benches were set at a grade of 200H:1V (0.5%), and were limited to a depth of 1.5 feet difference in elevation along the length of the bench. Using those limits, the letdown structures were spaced approximately 600 feet apart, with benches rising away in both directions from each letdown structure. Figure N-1 shows the locations of letdown structures. The first letdown ditch is expected to be built in line with the eastern side of Pond 1 in Cell 1. From this location, letdown structures are numbered proceeding clockwise around the footprint of the landfill. Ponds are located on Figure 1 and are numbered in the order they are expected to be constructed.

Table N-1 is a summary of the letdown structures and is set up to indicate which pond will serve each letdown structure. The letdown structure flows are directed to the nearest pond. Table N-1 lists:

- a location at a letdown structure or pond,
- the distance along the perimeter of the side-slope crest,
- the side slope area below the top of slope which is conservatively assumed to collect in the perimeter ditch at the letdown ditch,
- the side slope area below the top of slope is also assumed to flow into the perimeter ditch through the letdown structure,
- the sum of the total drainage area flowing in the letdown structure,
- the sum of all areas served by the perimeter ditch at and above the letdown structure,
- the flow contributed to the perimeter ditch at each letdown structure, and;
- the cumulative flow in the perimeter ditch at the location of each letdown structure.

The table is set up to allow convenient coordination with the tables estimating the water profiles in the perimeter ditch.

Capacity

The Rational Method was used to estimate the landfill's runoff. The rational method equation is:

$$Q = CIA$$

Where: Q is the flow rate (cfs)
C is the runoff coefficient (unitless)
I is the rainfall intensity (in/hr)
A is the drainage area (acres)

A runoff coefficient of $C=0.4$ is used and is considered representative for low to moderate permeability soils with emergent ground cover on steep slopes.

Areas served by side benches and letdowns are expected to be less than 11 acres each. For a 25-yr, 1-hr storm, the expected rainfall is 2.63 in/hr and the anticipated runoff from 11 acres is:

$$Q = 0.4 \times 2.63 \text{ in/hr} \times 11 \text{ ac} \times 43,560 \text{ ft}^2/\text{ac} \times 1 \text{ ft}/12 \text{ in} \times 1 \text{ hr}/3,600 \text{ s} = 11.67 \text{ cfs}$$

The 25-yr, 1-hr storm intensity (2.63 in/hr) is used as more conservative than the 25-yr, 24-hr storm intensity of 5.6 in. The 24-hr storm intensity would require the flow to be adjusted by dividing by 24 hours; $5.6 \text{ in}/24 \text{ hr} = 0.233 \text{ in/hr}$. The storm intensity table is found in Rainfall Frequency Atlas of the Midwest by Floyd A. Huff and James R. Angel, Table 7 (<http://www.sws.uiuc.edu/pubdoc/B/ISWSB-71.pdf>). Capacity for flow was evaluated for top of slope diversion berms, intermediate bench diversion berms (side benches) and letdown structures. The largest flow of 11.67 cfs is also used in Appendix M to test the stability of these structures for erosion during peak flow.

Manning's equation was used to calculate the flow capacity of the three types of drainage features: top of slope diversion berms; intermediate bench diversion berm; and letdown structures. Manning's equation is:

$$Q = (1.49/n)(A)(r_H)^{2/3}(s)^{1/2}$$

Where: Q is the flow rate (cfs)
n is Manning's coefficient of roughness (unitless)
A is the drainage area (ft^2)
 r_H is the hydraulic radius (ft), which equals A/P_w , where P_w is the wetted perimeter, and
s is the slope (ft/ft).

Manning's equation is also used to define the water profile in the perimeter ditch.

Top of Slope Diversion Berms

The purpose of the top of slope diversion berms is to inhibit rill erosion on the upper part of the landfill cap and at the top of the 3:1 slope. Diversion berms are placed on the cap to direct run-off to the letdown structures. The diversion berms are simple mounds of soil constructed as a V-notch channel. The berms are modeled with Manning's equation using a triangular cross-section with side slopes of 3:1 and 50:1 (2%). The following calculation shows the capacity of a berm carrying 0.5 ft. of water with a flow line of one-half percent (0.5%), using a typical n value of .020 for the coefficient of roughness, and an area of 6.63 sq. ft.

$$Q = (1.49/0.020)(6.63)(0.25)^{2/3}(0.005)^{1/2} = 13.9 \text{ cfs} > 11.67 \text{ cfs}$$

This capacity exceeds the flow anticipated at each individual letdown structure shown on Table N-1.

Intermediate Bench Diversion Berm (Side Benches)

The intermediate benches are 1.5 ft deep and have a flowline of one-half percent (0.5%). They have a triangular cross-section with side slopes of 10H:1V and 3H:1V. When full, they have a cross-sectional area of 14.625 sq. ft., a wetted perimeter of 19.8 ft and a hydraulic radius of 0.74 ft. The coefficient of roughness is 0.025.

$$Q = (1.49/0.025)(14.625)(0.74)^{2/3}(0.005)^{1/2} = 50.4 \text{ cfs} > 11.67 \text{ cfs}$$

This capacity exceeds the flow anticipated at each individual letdown structure shown on Table N-1.

Letdown Structure

The letdowns are 1.5 ft deep and have a maximum flowline slope of 33% (3:1). They have a trapezoidal cross-section with an 8 ft bottom and 3:1 side slopes. When full, they have a cross-sectional area of 18.8 sq. ft., a wetted perimeter of 17.5 ft and a hydraulic radius of 1.1 ft. The typical coefficient of roughness equal to 0.035 was used.

$$Q = (1.49/0.035)(18.8)(1.1)^{2/3}(0.33)^{1/2} = 492 \text{ cfs} > 11.67 \text{ cfs}$$

Table N-1 and Figure N-1 (see attached) show the estimated areas served and the estimated flows from each berm and letdown structure.

Perimeter Ditch

Because the perimeter ditch is long and flat and it is expected to flow at a "subcritical" level. Therefore, Manning's equation used alone does not model its capacity well. A combination of Manning's equation and Bernoulli's equation were used to describe the flow in the perimeter ditch. Bernoulli's equation is

$$H = P/\delta + v^2/2g + Z$$

Where: H is the energy measured as depth of water (ft.)

P is the pressure on the water, taken as zero for open systems

δ is gamma, the unit weight of water (lb/ft³)

v is the velocity of water (fps)

g is the gravity constant (32 fps²)

Z is the elevation of the fluid element (ft.)

Bernoulli's equations were used to estimate the energy at each letdown structure leading to a specific stormwater pond. Manning's equation was used to estimate the slope of the energy line between the letdown structures. The perimeter ditch was broken into sections between letdowns (see Figure N-1). The depth of flow at the structure was adjusted to estimate the slope of the energy line necessary to match the distances between letdown structures or a letdown structure

and the center of the entrance into a stormwater pond. The combination of these equations is used to evaluate the length of the perimeter ditch and the assumption of non-uniform flow.

The flow for the landfill, calculated using the rational method as described above, was proportionally divided between each section and is shown as a cumulative value approaching each pond.

An energy balance was applied to each section to determine the head loss and rise in depth. Bernoulli's and Manning's equations were used to calculate the depth of flow and elevation of the water level in the perimeter ditch. The attached tables summarize these calculations and show the estimated water elevations in each section (see Tables N-2 to N-7). Since these ponds are built at different times during the life of the landfill, consideration was given to the stormwater volumes to those ponds as each cell is constructed. The ponds generally serve the following cells:

| | | |
|----------|---------------|--------------------|
| • Pond 1 | Cells 1 and 2 | Tables N-2 and N-3 |
| • Pond 2 | Cells 3 and 4 | Tables N-4 and N-5 |
| • Pond 3 | Cells 3 and 4 | Tables N-6 and N-7 |

Ponds are placed around the Ameren Labadie Energy Center utility waste landfill where space allowed and to minimize the length of flow in the perimeter ditch. The ditch is modeled with a flat bottom width of 9 feet. At a 3:1 slope, two feet (2 ft.) of cover requires 6 feet of the perimeter ditch space. The difference is the placement of soil cover on the initial phases allows for subsequent development of cells without having the amount of infiltration on the caps. The maximum water elevation in the perimeter ditch for all modeled conditions is 485 ft., which is less than the perimeter berm top elevation of 488 ft.

Stormwater Inlet Crests

Runoff flow enters the ponds over stormwater inlet crests constructed in the top of the perimeter berm. These inlets were modeled as broad-crested weirs. Vennard suggests estimating the flow over a broad-crested weir by calculating the flow over the unit length of the weir using the following equation:

$$q = (2/3)^{3/2} \times g^{1/2} \times E^{3/2}$$

Where: q is the flow per unit width of a broad-crested weir (cfs/ft.)

g is the gravity constant (32 fps²)

E is the height of the energy line calculated for the entrance to the pond (ft.)

Since the constraints are dependent with not only the flow rate going into the stormwater ponds, but also the weir length of the pond, both elements must be considered. The stormwater collection ponds have the following minimum weir lengths at elevation 483 feet:

| | |
|---------|---------|
| Pond 1: | 217 ft. |
| Pond 2: | 65 ft. |
| Pond 3: | 300 ft. |

The lowest estimated energy grade line coming into any single pond is 0.511 ft. at the influent to Pond 1. Pond 1 has a weir length of 217 ft (see Table N-3). Pond 1 also has the largest design

flow at a combined, estimated 69.77 cfs (see Pond 1, Table N-1). Using the equation above, the capacity of the influent structure to Pond 1 is calculated as:

$$Q = (2/3)^{3/2} (32)^{1/2} (0.646)^{3/2} = 1.59 \text{ cfs/ft.}$$

$$1.59 \text{ cfs/ft} * 217 \text{ ft} = 345 \text{ cfs} > 69.77 \text{ cfs}$$

Therefore, the influent structure to Pond 1 has sufficient capacity for the anticipated design flow.

Pond 2 has the shortest weir length, with a weir length of 65 ft. Pond 2 has an estimated energy grade line of 1.064 ft. (see Pond 2, Table N-5). The combined, estimated design flow into Pond 2 is estimated at 50.37 cfs.

$$Q = (2/3)^{3/2} (32)^{1/2} (0.836)^{3/2} = 2.35 \text{ cfs/ft.}$$

$$2.35 \text{ cfs/ft} * 65 \text{ ft} = 152.75 \text{ cfs} > 50.37 \text{ cfs}$$

Therefore, the influent structure to Pond 2 has sufficient capacity for the anticipated design flow.

It is concluded that the influent structures for the stormwater collection ponds have adequate flow capacity based on their respective weir length and the estimated height of energy grade line entering the ponds.

Stormwater Ponds

Three stormwater ponds will be placed around the landfill for stormwater runoff storage and management. They are identified as Pond 1, collecting runoff from Cells 1 and 2; Pond 2, collecting runoff from Cells 3 and 4; and Pond 3, collecting runoff from Cells 3 and 4. Tables N-8 through N-10 provide stage-storage data for Ponds 1 through 3, respectively. Run-off volumes were calculated using Rational Method theory (i.e., run-off Volume=CIA, where I = rainfall in total inches). A runoff coefficient of C= 0.4 is considered representative of low to moderate permeability soils with emergent ground cover on steep slopes.

A runoff coefficient of C= 1 is used for the stormwater ponds to reflect that any direct rainfall to the pond surface will accumulate completely to the pond's stored volume.

The following table compiles the estimated, maximum runoff volumes to each pond during the 25-year, 24-hour design storm event of 5.6 inches. These pond volumes were checked to see if this volume is available at each respective pond to contain the design storm:

| | | | | |
|---------------|------------|-------------------|---------------|-----------------------|
| Pond 1 | 5.7 acres | 5.6 in.= 0.47 ft. | c=1 | 2.7 acre-feet |
| Cells 1 and 2 | 66.6 acres | 5.6 in.= 0.47 ft. | c=0.4 | 12.4 acre-feet |
| | | | Total= | 15.1 acre-feet |
| Pond 2 | 4.4 acres | 5.6 in.= 0.47 ft. | c=1 | 2.1 acre-feet |
| Cells 3 and 4 | 47.8 acres | 5.6 in.= 0.47 ft. | c=0.4 | 9.0 acre-feet |
| | | | Total= | 11.1 acre-feet |
| Pond 3 | 3.4 acres | 5.6 in.= 0.47 ft. | c=1 | 1.6 acre-feet |
| Cells 3 and 4 | 52.1 acres | 5.6 in.= 0.47 ft. | c=0.4 | 9.8 acre-feet |
| | | | Total= | 11.4 acre-feet |

The ponds have been designed with an inlet spillway elevation of 483 feet, and are to be maintained at a minimum 3 foot depth (water surface elevation of approximately 471 feet) to inhibit aquatic vegetation. Based on the stage-storage data found in Tables N-8, N-9 and N-10, the following initial maximum water surface elevations have been determined for each pond that represents the 25-year, 24-hour storm runoff volume. All maximum water elevations are well below a water surface elevation of 483 feet, which is the elevation of the bottom of the perimeter ditch. Therefore, if properly managed, the ponds have excess capacity for the anticipated 25-year, 24-hour storm runoff volume.

| Respective Pond | Min Elevation (ft.) | Max Elevation (ft.) | Corresponding Table |
|-----------------|---------------------|---------------------|---------------------|
| Pond 1 | 471 | 478 | N-8 |
| Pond 2 | 471 | 480 | N-9 |
| Pond 3 | 471 | 477 | N-10 |

Temporary Perimeter Ditch Crossings

As phased construction proceeds, the UWL operator may elect to retain interior berms and their top-of-berm roads during subsequent UWL phases. If interior berms are retained, it will be necessary to provide culverts through the intermediate berms at their intersection with the perimeter ditches. Preliminary culvert sizes have been estimates based on the arrangement of letdown ditches and ponds described by the previous discussion. For the purposes of these preliminary size estimates, we have assumed inlet control and one foot of headwater at the culvert inlets. These culvert sizes were estimated using standard hydraulic charts and equations, and the 25-year, 1-hour design storm event (2.63 in/hr).

| Culvert System | Letdown(s) | Accumulative Max. Flow (cfs) | Recommended Culvert Diameter (in.) |
|----------------------------|------------|------------------------------|------------------------------------|
| East Culvert-Cells 1 and 2 | 4,5,6,7 | 22.01 | 30 |
| West Culvert-Cells 1 and 2 | 7,8,9,10 | 26.22 | 36 |
| East Culvert-Cells 3 and 4 | 17 | 6.69 | 15 |
| West Culvert-Cells 3 and 4 | 25,26 | 14.62 | 24 |

TABLES

**Ameren Labadie Energy Center Utility Waste Landfill
Area and Flow At Each Letdown Structure
25-yr, 1-hr Event
Table N-1**

| Location | Distance | Side Slope Area | Top Area | Total Area | Total Area | Cumulative Area | Flow | |
|---|----------|-----------------|----------|------------|------------|-----------------|-------------------|---------------------|
| | (ft) | (ac) | (ac) | (sf) | (ac) | (ac) | in letdown, (cfs) | accumulative, (cfs) |
| LETDOWNS 1-11 (Cells 1 & 2) | | | | | | | | |
| Flow to Pond 1 | | | | | | | | |
| Rotating Clockwise from East Side of Outlet Pond 1 | | | | | | | | |
| Letdown 2 | 500 | 2.17 | 1.89 | 176796 | 4.06 | 4.06 | 4.31 | 35.00 |
| Letdown 3 | 940 | 2.75 | 5.42 | 356260 | 8.18 | 12.24 | 8.68 | 30.69 |
| Letdown 4 | 1450 | 2.11 | 3.14 | 228750 | 5.25 | 17.49 | 5.57 | 22.02 |
| Letdown 5 | 1850 | 2.73 | 1.40 | 180000 | 4.13 | 21.62 | 4.38 | 16.45 |
| Letdown 6 | 2500 | 2.51 | 1.91 | 192500 | 4.42 | 26.04 | 4.69 | 12.06 |
| Letdown 7 | 3000 | 2.53 | 4.42 | 302813 | 6.95 | 32.99 | 7.37 | 7.37 |
| Flow to Pond 1 | | | | | | | | |
| Rotating Counter Clockwise from East Side of Outlet Pond 1 | | | | | | | | |
| Letdown 1 | 220 | 4.19 | 2.48 | 290400 | 6.67 | 6.67 | 7.07 | 34.77 |
| Letdown 11 | 1020 | 4.19 | 4.15 | 363281 | 8.34 | 15.01 | 8.85 | 27.70 |
| Letdown 10 | 1550 | 2.48 | 4.82 | 317813 | 7.30 | 22.30 | 7.74 | 18.85 |
| Letdown 9 | 1950 | 3.80 | 2.97 | 295000 | 6.77 | 29.07 | 7.18 | 11.11 |
| Letdown 8 | 2920 | 2.59 | 1.11 | 161250 | 3.70 | 32.78 | 3.93 | 3.93 |
| LETDOWNS 12-29 (Cells 3 & 4) | | | | | | | | |
| Flow to Pond 3 | | | | | | | | |
| Rotating Clockwise from East side of Pond 3 | | | | | | | | |
| Letdown 14 | 0 | 3.24 | 2.85 | 265200 | 6.09 | 6.09 | 6.46 | 18.61 |
| Letdown 15 | 500 | 2.81 | 2.81 | 244400 | 5.61 | 11.70 | 5.95 | 12.16 |
| Letdown 16 | 950 | 2.81 | 3.04 | 254800 | 5.85 | 17.55 | 6.20 | 6.20 |
| Flow to Pond 2 | | | | | | | | |
| Rotating Counter-Clockwise from West side of Outlet Pond 2 | | | | | | | | |
| Letdown 18 | 860 | 4.82 | 2.18 | 305000 | 7.00 | 7.00 | 7.43 | 14.12 |
| Letdown 17 | 1360 | 2.81 | 3.50 | 274860 | 6.31 | 13.31 | 6.69 | 6.69 |
| Flow to Pond 2 | | | | | | | | |
| Rotating Clockwise from East side of Outlet Pond 2 | | | | | | | | |
| Letdown 19 | 600 | 4.53 | 1.42 | 259200 | 5.95 | 5.95 | 6.31 | 36.25 |
| Letdown 20 | 1100 | 2.87 | 4.99 | 342300 | 7.86 | 13.81 | 8.34 | 29.94 |
| Letdown 21 | 1600 | 2.87 | 1.03 | 170000 | 3.90 | 17.71 | 4.14 | 21.60 |
| Letdown 22 | 2100 | 2.87 | 1.26 | 180000 | 4.13 | 21.84 | 4.38 | 17.46 |
| Letdown 23 | 2600 | 3.46 | 0.09 | 154800 | 3.55 | 25.40 | 3.77 | 13.08 |
| Letdown 24 | 3040 | 5.17 | 0.53 | 248000 | 5.69 | 31.09 | 6.04 | 9.31 |
| Letdown 25 | 3790 | 2.70 | 3.47 | 268600 | 6.17 | 33.82 | 6.54 | 3.27 |
| Flow to Pond 3 | | | | | | | | |
| Rotating Counter-Clockwise from East-Side of Outlet Pond 3 | | | | | | | | |
| Letdown 13 | 320 | 1.32 | 0.22 | 67200 | 1.54 | 1.54 | 1.64 | 32.61 |
| Letdown 12 | 960 | 3.40 | 1.32 | 205900 | 4.73 | 6.27 | 5.01 | 30.97 |
| Letdown 29 | 1780 | 2.70 | 1.21 | 170000 | 3.90 | 10.17 | 4.14 | 25.96 |
| Letdown 28 | 2240 | 2.53 | 2.53 | 220000 | 5.05 | 15.22 | 5.36 | 21.82 |
| Letdown 27 | 2640 | 2.41 | 2.41 | 210000 | 4.82 | 20.04 | 5.11 | 16.46 |
| Letdown 26 | 3120 | 1.89 | 5.72 | 331600 | 7.61 | 27.66 | 8.08 | 11.35 |
| Letdown 25 | 3330 | 2.70 | 3.47 | 268600 | 6.17 | 33.82 | 6.54 | 3.27 |

Inputs 25-yr, 1-hr storm


| | | |
|-----------|------|----------|
| Intensity | 2.63 | in |
| C Factor | 0.4 | unitless |

**Ameren Labadie Energy Center Utility Waste Landfill
Perimeter Ditch Water Profile: 25-yr, 1-hr event
Elevation for Stated Flow
Clockwise from Pond 1
Table N-2**

| | | | S _{s, left} = 3 | | S _{s, right} = 3 | | Base Width (ft) = 9 | | Mannings N = 0.02 | | So (ft) = 0 | | Runoff Factor for 2.63 in/ hr rainfall= 0.017 | | | | | |
|-----------|-------|--------------------------------|------------------------------|------------------|---------------------------|-------|------------------------|--------------------|------------------------------|--------------------------------|-------------|----------|---|-------------------|------------------|-----------|--------------------------|-------|
| Elevation | Depth | Channel Bottom Elevation | Slope of Water Surface | Adjusted Base | Adjusted Height | Area | Velocity | v ² /2g | Specific Energy | Hydraulic Radius | Slope | S-So | Distance | Total Distance | True Distance | Location | Distance from Culvert | Q |
| | | | | | | | Average Velocity | | Change in Specific Energy | Average Hydraulic Radius | | | | | | | | |
| (ft) | (ft) | (ft) | (ft/ft) | (ft) | (ft) | (sf) | (fps) | (ft) | (ft) | (ft) | (ft/ft) | (ft/ft) | (ft) | (ft) | (ft) | | (ft) | (cfs) |
| 483.59 | 0.59 | 483 | | | | 6.35 | 1.898 | 0.0560 | 0.646 | 0.499 | | | | 0 | 0 | Pond 1 | 0 | 12.06 |
| | 0.63 | | 0.0011928 | | | | 2.082 | | 0.654 | 0.712 | 1.24E-03 | 1.24E-03 | 528 | 528 | | | | |
| 484.22 | 1.22 | 483 | | 9.00 | 1.2200 | 15.45 | 2.266 | 0.0797 | 1.300 | 0.924 | | | | | 500 | Letdown 2 | 500 | 35.00 |
| | 0.31 | | 0.0007271 | | | | 1.871 | | 0.264 | 1.019 | 6.19E-04 | 6.19E-04 | 426 | 955 | | | | |
| 484.53 | 1.53 | 483 | | 9.00 | 1.5300 | 20.79 | 1.476 | 0.0338 | 1.564 | 1.113 | | | | | 940 | Letdown 3 | 940 | 30.69 |
| | 0.13 | | 0.0002606 | | | | 1.212 | | 0.110 | 1.152 | 2.21E-04 | 2.21E-04 | 499 | 1453 | | | | |
| 484.66 | 1.66 | 483 | | 9.00 | 1.6600 | 23.21 | 0.949 | 0.0140 | 1.674 | 1.190 | | | | | 1450 | Letdown 4 | 1450 | 22.02 |
| | 0.04 | | 0.0001138 | | | | 0.817 | | 0.033 | 1.202 | 9.48E-05 | 9.48E-05 | 351 | 1805 | | | | |
| 484.70 | 1.70 | 483 | | 9.00 | 1.7000 | 23.97 | 0.686 | 0.0073 | 1.707 | 1.214 | | | | | 1850 | Letdown 5 | 1850 | 16.45 |
| | 0.04 | | 5.238E-05 | | | | 0.587 | | 0.036 | 1.225 | 4.76E-05 | 4.76E-05 | 764 | 2568 | | | | |
| 484.74 | 1.74 | 483 | | 9.00 | 1.7400 | 24.74 | 0.487 | 0.0037 | 1.744 | 1.237 | | | | | 2500 | Letdown 6 | 2500 | 12.06 |
| | 0.01 | | 2.724E-05 | | | | 0.392 | | 0.008 | 1.240 | 2.09E-05 | 2.09E-05 | 367 | 2936 | | | | |
| 484.75 | 1.75 | 483 | | 9.00 | 1.7500 | 24.94 | 0.296 | 0.0014 | 1.751 | 1.243 | | | | | 3000 | Letdown 7 | 3000 | 7.37 |

Notes:

1. Rainfall event used is 25-yr, 1-hr storm which produces 2.63 inches of rain.
2. Longitudinal slope of channel assumed to be as stated for So.
3. Flows are split generally at half the distance between the entrances to the pond along the perimeter ditch.
4. Flows coming to a letdown structure and from below the bench served by the letdown structure are combined as the flow at the letdown structure for modeling purposes.
5. Model is adapted from Illustrative problem on page 380 in "Elementary Fluid Mechanics" by John Vennard, Wiley and Sons, 1961.




Ameren Labadie Energy Center Utility Waste Landfill
Perimeter Ditch Water Profile: 25-yr, 1-hr event
Elevation for Stated Flow
Counter Clockwise from Pond 1
Table N-3

| | | | S _{a, left} = 3 | | S _{a, right} = 3 | | Base Width (ft) = 9 | | Mannings N = 0.02 | | So (ft) = 0 | | Runoff Factor for 2.63 in/ hr rainfall= 0.017 | | | | | |
|-----------|-------|--------------------------|--------------------------|---------------|---------------------------|-------|------------------------|--------|---------------------------|--------------------------|-------------|----------|---|----------------|---------------|------------|-----------------------|-------|
| Elevation | Depth | Channel Bottom Elevation | Slope of Water Surface | Adjusted Base | Adjusted Height | Area | Velocity | v²/2g | Specific Energy | Hydraulic Radius | Slope | S-So | Distance | Total Distance | True Distance | Location | Distance from Culvert | Q |
| | | | | | | | Average Velocity | | Change in Specific Energy | Average Hydraulic Radius | | | | | | | | |
| (ft) | (ft) | (ft) | (ft/ft) | (ft) | (ft) | (sf) | (fps) | (ft) | (ft) | (ft) | (ft/ft) | (ft/ft) | (ft) | (ft) | (ft) | | (ft) | (cfs) |
| 483.59 | 0.59 | 483 | | | | 6.35 | 1.898 | 0.0560 | 0.646 | 0.499 | | | | 0 | 0 | Pond 1 | 0 | 12.06 |
| | 0.37 | | 0.0016659 | | | | 2.473 | | 0.458 | 0.628 | 2.06E-03 | 2.06E-03 | 222 | 222 | | | | |
| 483.96 | 0.96 | 483 | | 9.00 | 0.9600 | 11.40 | 3.049 | 0.1443 | 1.104 | 0.757 | | | | | 220 | Letdown 1 | 220 | 34.77 |
| | 0.76 | | 0.0009613 | | | | 2.093 | | 0.636 | 0.991 | 8.04E-04 | 8.04E-04 | 791 | 1013 | | | | |
| 484.72 | 1.72 | 483 | | 9.00 | 1.7200 | 24.36 | 1.137 | 0.0201 | 1.740 | 1.225 | | | | | 1020 | Letdown 11 | 1020 | 27.70 |
| | 0.07 | | 0.0001422 | | | | 0.935 | | 0.058 | 1.246 | 1.18E-04 | 1.18E-04 | 492 | 1505 | | | | |
| 484.79 | 1.79 | 483 | | 9.00 | 1.7900 | 25.72 | 0.733 | 0.0083 | 1.798 | 1.266 | | | | | 1550 | Letdown 10 | 1550 | 18.85 |
| | 0.03 | | 5.652E-05 | | | | 0.578 | | 0.019 | 1.273 | 4.40E-05 | 4.40E-05 | 442 | 1947 | | | | |
| 484.82 | 1.82 | 483 | | 9.00 | 1.8150 | 26.22 | 0.424 | 0.0028 | 1.818 | 1.280 | | | | | 1950 | Letdown 9 | 1950 | 11.11 |
| | 0.02 | | 1.269E-05 | | | | 0.286 | | 0.013 | 1.285 | 1.06E-05 | 1.06E-05 | 1182 | 3129 | | | | |
| 484.83 | 1.83 | 483 | | 9.00 | 1.8300 | 26.52 | 0.148 | 0.0003 | 1.830 | 1.289 | | | | | 2920 | Letdown 8 | 2920 | 3.93 |

Notes:

1. Rainfall event used is 25-yr, 1-hr storm which produces 2.63 inches of rain.
2. Longitudinal slope of channel assumed to be as stated for S_o .
3. Flows are split generally at half the distance between the entrances to the pond along the perimeter ditch.
4. Flows coming to a letdown structure and from below the bench served by the letdown structure are combined as the flow at the letdown structure for modelling purposes.
5. Model is adapted from Illustrative problem on page 380 in "Elementary Fluid Mechanics" by John Vennard, Wiley and Sons, 1961.




Ameren Labadie Energy Center Utility Waste Landfill
Perimeter Ditch Water Profile: 25-yr, 1-hr event
Elevation for Stated Flow
Clockwise from Pond 2
Table N-4

| | | | $S_{s, \text{left}} = 3$ | | $S_{s, \text{right}} = 3$ | | Base Width (ft) = 9 | | Mannings N = 0.02 | | S_o (ft) = 0 | | Runoff Factor for 2.63 in/ hr rainfall= 0.017 | | | | | |
|-----------|-------|--------------------------|--------------------------|---------------|---------------------------|-------|---------------------|----------|---------------------------|--------------------------|----------------|----------|---|----------------|---------------|------------|-----------------------|-------|
| Elevation | Depth | Channel Bottom Elevation | Slope of Water Surface | Adjusted Base | Adjusted Height | Area | Velocity | $v^2/2g$ | Specific Energy | Hydraulic Radius | Slope | S-So | Distance | Total Distance | True Distance | Location | Distance from Culvert | Q |
| | | | | | | | Average Velocity | | Change in Specific Energy | Average Hydraulic Radius | | | | | | | | |
| (ft) | (ft) | (ft) | (ft/ft) | (ft) | (ft) | (sf) | (fps) | (ft) | (ft) | (ft) | (ft/ft) | (ft/ft) | (ft) | (ft) | (ft) | | (ft) | (cfs) |
| 483.80 | 0.80 | 483 | | | | 9.12 | 3.975 | 0.2453 | 1.045 | 0.649 | | | | 0 | 0 | Pond 2 | 0 | 36.3 |
| | 1.03 | | 0.001709 | | | | 2.671 | | 0.814 | 0.969 | 1.35E-03 | 1.35E-03 | 603 | 603 | 600 | | | |
| 484.83 | 1.83 | 483 | | 9.00 | 1.8300 | 26.52 | 1.367 | 0.0290 | 1.859 | 1.289 | | | | | | Letdown 19 | 600 | 36.3 |
| | 0.10 | | 0.000208 | | | | 1.208 | | 0.088 | 1.317 | 1.83E-04 | 1.83E-04 | 481 | 1083 | 1100 | | | |
| 484.93 | 1.93 | 483 | | 9.00 | 1.9300 | 28.54 | 1.049 | 0.0171 | 1.947 | 1.346 | | | | | | Letdown 20 | 1100 | 29.9 |
| | 0.06 | | 0.000111 | | | | 0.887 | | 0.051 | 1.363 | 9.44E-05 | 9.44E-05 | 541 | 1624 | 1600 | | | |
| 484.99 | 1.99 | 483 | | 9.00 | 1.9900 | 29.79 | 0.725 | 0.0082 | 1.998 | 1.380 | | | | | | Letdown 21 | 1600 | 21.6 |
| | 0.03 | | 5.5E-05 | | | | 0.650 | | 0.027 | 1.389 | 4.94E-05 | 4.94E-05 | 545 | 2170 | 2100 | | | |
| 485.02 | 2.02 | 483 | | 9.00 | 2.0200 | 30.42 | 0.574 | 0.0051 | 2.025 | 1.397 | | | | | | Letdown 22 | 2100 | 17.5 |
| | 0.01 | | 3.76E-05 | | | | 0.501 | | 0.008 | 1.400 | 2.90E-05 | 2.90E-05 | 266 | 2436 | 2600 | | | |
| 485.03 | 2.03 | 483 | | 9.00 | 2.0300 | 30.63 | 0.427 | 0.0028 | 2.033 | 1.403 | | | | | | Letdown 23 | 2600 | 13.1 |
| | 0.02 | | 1.68E-05 | | | | 0.364 | | 0.014 | 1.407 | 1.52E-05 | 1.52E-05 | 891 | 3327 | 3040 | | | |
| 485.05 | 2.05 | 483 | | 9.00 | 2.0450 | 30.95 | 0.301 | 0.0014 | 2.046 | 1.411 | | | | | | Letdown 24 | 3040 | 9.3 |
| | 0.00 | | 5.91E-06 | | | | 0.150 | | 0.001 | 1.412 | 2.59E-06 | 2.59E-06 | 423 | 3749 | 3790 | | | |
| 485.05 | 2.05 | 483 | | 9.00 | 2.0475 | 31.00 | 0.000 | 0.0000 | 2.048 | 1.413 | | | | | | Letdown 25 | 3790 | 3.3 |

Notes:

1. Rainfall event used is 25-yr, 1-hr storm which produces 2.63 inches of rain.
2. Longitudinal slope of channel assumed to be as stated for S_o .
3. Flows are split generally at half the distance between the entrances to the pond along the perimeter ditch.
4. Flows coming to a letdown structure and from below the bench served by the letdown structure are combined as the flow at the letdown structure for modeling purposes.
5. Model is adapted from Illustrative problem on page 380 in "Elementary Fluid Mechanics" by John Vennard, Wiley and Sons, 1961.




Ameren Labadie Energy Center Utility Waste Landfill
Perimeter Ditch Water Profile: 25-yr, 1-hr event
Elevation for Stated Flow
Counter Clockwise from Pond 2
Table N-5

| | | | $S_{s, \text{left}} = 3$ | | $S_{s, \text{right}} = 3$ | | Base Width (ft) = 9 | | Mannings N = 0.02 | | S_o (ft) = 0 | | Runoff Factor for 2.63 in/ hr rainfall= 0.017 | | | | | |
|-----------|-------|--------------------------|--------------------------|---------------|---------------------------|-------|---------------------|----------|---------------------------|--------------------------|----------------|----------|---|----------------|---------------|------------|-----------------------|-------|
| Elevation | Depth | Channel Bottom Elevation | Slope of Water Surface | Adjusted Base | Adjusted Height | Area | Velocity | $v^2/2g$ | Specific Energy | Hydraulic Radius | Slope | S-So | Distance | Total Distance | True Distance | Location | Distance from Culvert | Q |
| | | | | | | | Average Velocity | | Change in Specific Energy | Average Hydraulic Radius | | | | | | | | |
| (ft) | (ft) | (ft) | (ft/ft) | (ft) | (ft) | (sf) | (fps) | (ft) | (ft) | (ft) | (ft/ft) | (ft/ft) | (ft) | (ft) | (ft) | | (ft) | (cfs) |
| 483.80 | 0.80 | 483 | | | | 9.12 | 1.530 | 0.0363 | 0.836 | 0.649 | | | | 0 | 0 | Pond 2 | 0 | 14 |
| | 0.36 | | 0.000431 | | | | 1.253 | | 0.338 | 0.767 | 4.05E-04 | 4.05E-04 | 836 | 836 | 860 | | | |
| 484.16 | 1.16 | 483 | | 9.00 | 1.1600 | 14.48 | 0.975 | 0.0148 | 1.175 | 0.886 | | | | | | Letdown 18 | 860 | 14 |
| | 0.06 | | 0.000128 | | | | 0.704 | | 0.048 | 0.905 | 1.03E-04 | 1.03E-04 | 468 | 1304 | 1360 | | | |
| 484.22 | 1.22 | 483 | | 9.00 | 1.2200 | 15.45 | 0.433 | 0.0029 | 1.223 | 0.924 | | | | | | Letdown 17 | 1360 | 7 |

Notes:

1. Rainfall event used is 25-yr, 1-hr storm which produces 2.63 inches of rain.
2. Longitudinal slope of channel assumed to be as stated for S_o .
3. Flows are split generally at half the distance between the entrances to the pond along the perimeter ditch.
4. Flows coming to a letdown structure and from below the bench served by the letdown structure are combined as the flow at the letdown structure for modeling purposes.
5. Model is adapted from illustrative problem on page 380 in "Elementary Fluid Mechanics" by John Vennard, Wiley and Sons, 1961.



Ameren Labadie Energy Center Utility Waste Landfill
Perimeter Ditch Water Profile: 25-yr, 1-hr event
Elevation for Stated Flow
Clockwise from Pond 3
Table N-6

| | | | $S_{s, \text{left}} = 3$ | | $S_{s, \text{right}} = 3$ | | Base Width (ft) = 9 | | Mannings N = 0.02 | | S_o (ft) = 0 | | Runoff Factor for 2.63 in/ hr rainfall= 0.017 | | | | | |
|-----------|-------|--------------------------|--------------------------|---------------|---------------------------|-------|---------------------|----------|---------------------------|--------------------------|----------------|----------|---|----------------|---------------|------------|-----------------------|-------|
| Elevation | Depth | Channel Bottom Elevation | Slope of Water Surface | Adjusted Base | Adjusted Height | Area | Velocity | $v^2/2g$ | Specific Energy | Hydraulic Radius | Slope | S-So | Distance | Total Distance | True Distance | Location | Distance from Culvert | Q |
| | | | | | | | Average Velocity | | Change in Specific Energy | Average Hydraulic Radius | | | | | | | | |
| (ft) | (ft) | (ft) | (ft/ft) | (ft) | (ft) | (sf) | (fps) | (ft) | (ft) | (ft) | (ft/ft) | (ft/ft) | (ft) | (ft) | (ft) | | (ft) | (cfs) |
| 483.72 | 0.72 | 483 | | | | 8.04 | 1.742 | 0.0471 | 0.767 | 0.593 | | | | 0 | 0 | Pond 3 | 0 | 14 |
| | 0.00 | | 0 | | | | 2.029 | | 0.036 | 0.593 | 1.50E-03 | 1.50E-03 | 24 | 24 | 0 | | | |
| 483.72 | 0.72 | 483 | | 9.00 | 0.7200 | 8.04 | 2.317 | 0.0833 | 0.803 | 0.593 | | | | | | Letdown 14 | 0 | 19 |
| | 0.41 | | 0.000848 | | | | 1.592 | | 0.338 | 0.730 | 7.00E-04 | 7.00E-04 | 483 | 508 | 500 | | | |
| 484.13 | 1.13 | 483 | | 9.00 | 1.1300 | 14.00 | 0.868 | 0.0117 | 1.142 | 0.867 | | | | | | Letdown 15 | 500 | 12 |

Notes:

1. Rainfall event used is 25-yr, 1-hr storm which produces 2.63 inches of rain.
2. Longitudinal slope of channel assumed to be as stated for S_o .
3. Flows are split generally at half the distance between the entrances to the pond along the perimeter ditch.
4. Flows coming to a letdown structure and from below the bench served by the letdown structure are combined as the flow at the letdown structure for modeling purposes.
5. Model is adapted from Illustrative problem on page 380 in "Elementary Fluid Mechanics" by John Vennard, Wiley and Sons, 1961.

