SPECIFICATIONS

Effective Sept. 2, 2002 Supercedes April 1, 2001 1830 Centennial Ave. Hastings, NE 68901 Ph: 402-462-2227 Fax: 402-462-5529 Toll Free: 866-851-2227 centennialplastics.com



CenCore HDPE

HDPE 3408 — ASTM D2239 and ASTM D2737

- Flexible polyethylene pipe and tubing
- Produced from only the finest virgin material
- Backed by a **50-YEAR WARRANTY**
- Natural Virgin Core with Blue Virgin Exterior

00/125 P.	SI ASTM D2239	PE3408	SIDR11.	5 Premium Grade				
		1/2	2"	3/4"	1"	1-1/4"	1-1/2"	2"
	O.D.	O.D. 0.742"		.968"	1.231"	1.620"	1.890"	2.427"
	I.D.	I.D. 0.622" Wall 0.060"		.824"	1.049"	1.380"	1.610"	2.067"
	Wall			.072"	.091"	.120"	.140"	.180"
	Wt/Ft 0.057#		7#	.090#	.143#	.246#	.330#	.544#
	Coil Lengths		00 ft.	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.
60 PSI	ASTM D2239	PE3408	SIDR9	Premium Grade				
		1/2	2"	3/4"	1"	1-1/4"	1-1/2"	2"
O.D. I.D. Wall		N/A		1.008"	1.283"	1.686"	1.968"	2.527"
		N/A		.824"	1.049"	1.380"	1.610"	2.067"
		N/A		.092"	.117"	.153"	.179"	.230"
Wt/Ft		N/A		.116#	.186#	.320#	.430#	.710#
	Coil Lengths	N/	A	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.
200 PSI*	ASTM D2239	PE3408	SIDR7	Premium Grade				
		1/2	2"	3/4"	1"	1-1/4"	1-1/2"	2"
	O.D.	N/A		1.060"	1.349"	1.774"	2.070"	2.657"
	I.D.	N/.	A	.824"	1.049"	1.380"	1.610"	2.067"
	Wall	N/.	A	.118"	.150"	.197"	.230"	.295"
Wt/Ft		N/A		.152#	.246#	.424#	.578#	.952#
	Coil Lengths	N/.	A	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.
200 PSI*	ASTM D2737	PE3408	SDR9 C	TS Premium Grad	de			
		1/2	2"	3/4"	1"	1-1/4"	1-1/2"	2"
	O.D.		5"	.875"	1.125"	1.375"	1.625"	2.125"
I.D. Wall		.487"		.681"	.875"	1.069"	1.263"	1.653"
		.069"		.097"	.125"	.153"	.181"	.236"
		.053#			470 "	05.4."	050#	(00 //
	Wt/Ft	.05	3#	.103#	.170#	.254#	.353#	.602#

Note: CenCore SIDR 11.5, SIDR 9 and SIDR 7 are suitable for connections with insert fittings and clamps.

Note: CenCore SDR 9 CTS is suitable for connections with CTS compression fittings.

